Digital Multimeter

TENMA™

Features:

- 3 ¾ digit LCD (63 mm × 31 mm), 5999 count
- Auto / manual ranging selector
- Display back light
- Over moulded cases
- Diode, continuity buzzer and data hold
- Capacitance measurement
- Temperature measurement
- Frequency measurement
- RS-232 PC interface
- 1-year warranty
- Meets IEC 1010, 1,000 V CAT II, 600 V CAT III
- CE compliant
- Fused 10 A range
- RS-232C
- Relative Mode
- Full Icon display
- Sleep mode
- Low battery display
- Input impedance for DCV : approximately 10 MΩ
- Power : 9 V battery (6F22) included
- Weight : Approximately 312 g
- Size : 177 mm × 73.5 mm × 35 mm
- Includes : Test leads, manual, point contact temperature probe, test clip, RS-232C cable and software

Function	Range	Accuracy
DC Voltage	600 mV, 6 V, 60 V, 600 V, 1,000 V	± (0.5% +3)
AC Voltage	600 mV, 6 V, 60 V, 600 V, 1,000 V	± (1% +2)
DC Current	60 mA, 600 mA, 10 A	± (1.2% +3)
AC Current	60 mA, 600 mA, 10 A	± (2% +5)
Resistance	600 Ω, 6 kΩ, 600 kΩ, 6 MΩ, 60 MΩ	± (1% +2)
Capacitance	6 nF, 60 nF, 600 nF, 6 µF, 60 µF, 600 µF, 6 mF	± (4% +3)
Frequency	6 KHz, 60 KHz, 600 KHz, 6 MHz, 60 MHz	± (0.05% +3)
Temperature °C	-40°C to 1,000°C	± (1% +3)

Part Number Table

Description	Part Number
Multimeter, Digital	72-7750

תיאור פריט: רב מודד דיגיטלי PRO II SERIES 72-7750
יצרן: TENMA
דגם: 72-7750
מק"ט טלמיר: 0260347
מיקום באתר: ציוד בדיקה ומכשירי מדידה / רבי מודדים וצבתות זרם / רבי מודדים MULTIMETERS
יבואן: טלמיר אלקטרוניקה בע"מ

© כל הזכויות שמורות - טלמיר אלקטרוניקה בע"מ