

Oscilloscope

Talmir Order Code: 2656412



Features:

- 40MHz high bandwidth with 2 channels
- 100MSPS real time sampling rate
- Multi-language support, easy to use
- USB2.0 interface, no external power required
- 23 measurement functions, PASS/FAIL check, FFT
- OS: Windows NT, Windows 2000, Windows XP, Windows 7
- Labview/VB/VC SDK

Specifications:

	Model	72-10155
Acquisition	Sample Mode	Real-Time Sample
	Sample Rate	100MSPS
	Average	N acquisitions, all channels simultaneously, N is selectable from 1-128
Input	Input Coupling	DC, AC, GND
	Input Impedance	Resistance: 1M Ω ; Capacitance: 25pF
	PP-80,PP-150,PP-200 Probe Attenuation	10X
	Probe Attenuation Factors	1X, 10X
	Maximum Input Voltage	35Vpk (DC + peak)
Horizontal	Scanning Speed Range(Sec/Div)	4ns/div ~ 1h/div(1-2-4 sequences)
	Sample Rate and Delay Time Accuracy	± 50 ppm(any interval ≥ 1 ms)
	Wave form Interpolation	Step, Linear, Sin(x)/x
	Memory Depth(Sample Points)	10K : available all timebase; 32K : 40 μ s/div-400ms/div(Dual channel); 20 μ s/div-400ms/div(Signal channel); 64K : 40 μ s/div-400ms/div
Vertical	Analog Bandwidth	40MHz (-3dB)
	A/D converter	8 bit resolution
	Vertical Scale(Volt/div) Range	10mV ~ 5V/div @ x1 probe(1,2,5 sequence); 100mV ~ 50V/div @ x10 probe
	Position Range	± 4 division
	Selectable Analog Bandwidth Limit(typical)	20MHz
	Lower Frequency Response(-3dB)	≤ 10 Hz(at input BNC)
	Rise Time at BNC(typical)	≤ 8.8 ns
	DC Gain Accuracy	$\pm 3\%$



Oscilloscope



Trigger	Trigger Source		CH1,CH2, EXT
	Trigger Mode		Auto, Normal and Single
	Trigger Type		Edge trigger: Rising edge, falling edge.
	Trigger Sensitivity		0.02 div increments
	Trigger Level Range		±4V
	Trigger Level Accuracy		±4 division
Measurement	Cursor Measure		Amplitude difference between cursors (ΔV); Time difference between cursors (Δt); Reciprocal of Δt in Hertz ($1/\Delta t$) (Cross, Trace, Horizontal, Vertical)
	Auto Measure	Voltage	Vp-p, Vmax, Vmin, Vmean, Vamp, Vtop, Vbase, Vmid, Vrms, Vcrms, Preshoot, Overshoot
		Time	Frequency, Period, Rise Time(10%~90%), Fall Time(10%~90%), Positive Width, Negative Width, Duty Cycl
	Environmental	Temperature	
Cooling Method		Forced air	
Humidity		Below +35°C, ≤90% relative humidity; +35°C to +40°C, ≤60% relative humidity	
Altitude		Operating: 3,000m or below; Non-operating: 15,000m or below	
Mechanical	Size		190mm(L)×100mm(W)×35mm(H)
	Heavy		Without Packaged 0.29kg; Packaged 0.9kg;
Accessories	Probe		X1, X10 two passive probes. The passive probes have a 6MHz bandwidth (rated 100Vrms CAT III) when the switch is in the X1 position, and a maximum bandwidth (rated 300Vrms CAT II) when the switch is in the X10 position. Each probe consists of all necessary fittings
	USB Line		A USB A-B line, used to connect external devices with USB-B interface like a printer or to establish communications between PC and the oscilloscope.
	Installation CD		A software installation CD and it also contains the user manual for the Tenma Oscilloscope.

Part Number Table

Description	Part Number
Oscilloscope, PC, 2 Channel, 40MHz	72-10155

ציוד בדיקה ומכשירי מדידה / אוסילוסקופים / אוסילוסקופים מבוססי PC / אוסילוסקופ מבוסס PC – דו ערוצי – TEMNA 40MHz
טלמיר אלקטרוניקה בע"מ

