

# 2 Channel 0-32V/0-5A Power Supply Unit



## Specifications:

Basic Functions	Channel	Best Accuracy
Output Voltage	CH1,CH2	0 to 32V
Output Current	CH1,CH2	0 to 5A
Overload Eeeect		CV $\leq 1 \cdot 10^{-4} + 2mV$ , CC $\leq 2mA$
Ripple & Noise		CV $\leq 1mV_{rms}$ , CC $\leq 1mA_{rms}$
Regulation		CV - 20mV (Typical Value), CC - 50mA (Typical Value)
Tracking Error		$5 \cdot 10^{-3} + 2mV$
Reliability		MTBF (e) : $\geq 2,000$ hours
Other Features		Dual Output, Series or Parallel Operation, Current Limitation, Auto Switching Between Voltage and Current Operation

## General Characteristics:

Power	: AC 230V $\pm 10\%$ , 50Hz $\pm 4\%$ (UK/Europe); AC 120V $\pm 10\%$ , 60Hz $\pm 4\%$ (US)
Product Colour	: Orange and Grey
Product Net Weight	: 4kg
Product Size	: 210mm $\times$ 152mm $\times$ 305mm
Standard Accessories	: Test Leads, English Manual, Power Cord 1 $\times$ UK + 1 $\times$ Euro (for UK/Europe); 1 $\times$ US (for US only)
Standard Packing	: Gift Box
Standard Quantity	: 1pc

## Part Number Table

Description	Part Number
2 Channel 0-32V/0-5A Power Supply Unit	72-8700A

מיקום הפריט: ציוד בדיקה ומכשירי מדידה / ספקי כוח מעבדתיים / ספקי כוח מעבדתיים – שתי יציאות  
תיאור הפריט: ספק כוח מעבדתי כפול 0-32V, 0-5A  
יצרן: TENMA  
מק"ט יצרן: 72-8700A  
יבואן: טלמיר אלקטרוניקה בע"מ