

3 Channel 0-32V/0-3A Power Supply Unit



Specifications:

Basic Functions	Channel	Best Accuracy
Output Voltage	CH1, CH2	0 to 32V
	CH3	5V
Output Current	CH1, CH2	0 to 3A
	CH3	2A
Overload Eeeect		CV $\leq 1 \cdot 10^{-4} + 2mV$, CC $\leq 2mA$
Ripple & Noise		CV $\leq 1mV_{rms}$, CC $\leq 1mArms$
Regulation		CV - 20mV (Typical Value), CC - 50mA (Typical Value)
Tracking Error		$5 \cdot 10^{-3} + 2mV$
Reliability		MTBF (e) : ≥ 2000 hours
Other Features		Triple Output, Series or Parallel Operation, Current Limitation, Auto Switching Between Voltage and Current Operation

General Characteristics:

Power	: AC 230V $\pm 10\%$, 50Hz $\pm 4\%$ (UK/Europe); AC 120V $\pm 10\%$, 60Hz $\pm 4\%$ (US)
Product Colour	: Orange and Grey
Product Net Weight	: 4kg
Product Size	: 210mm \times 152mm \times 305mm
Standard Accessories	: Test Leads, English Manual, Power Cord 1 \times UK + 1 \times Euro (for UK/Europe); 1 \times US (for US Only)
Standard Packing	: Gift Box
Standard Quantity	: 1pc

Part Number Table

Description	Part Number
3 Channel 0-32V/0-3A Power Supply Unit	72-8695A

מיקום הפריט: ציוד בדיקה ומכשירי מדידה / ספקי כוח מעבדתיים / ספקי כוח מעבדתיים – שלוש יציאות
 תיאור הפריט: ספק כוח מעבדתי כפול 0-3A , 1-32V + יציאה קבועה 5V 2A
 יצרן: TENMA
 מק"ט יצרן: 72-8695A
 יבואן: טלמיר אלקטרוניקה בע"מ