

# Pre-Heater



## Features:

- Quick heating, up to 350°C only in 10 s
- Temperature sensor keeps the output temperature stable
- Optional cool flow can preheat and cool chip
- Working with AT reworking station to deal with BGA and chip IC
- Smart and compact design and appearance, easy to carry
- Automatic temperature control, can work continuously working for long hours, not affecting the function of the device and the temperature of panel won't exceed the standard temperature

## Apply

R and D  
Production  
Lab of scientific research

## Specifications:

Input voltage : 220 V ±10%, 50 Hz / 110 V ±10% 60 Hz  
 Temperature range : 100 to 350°C  
 Air output range : 0.18 m<sup>3</sup> / mins  
 Output power : 540 W  
 Dimension : 170 × 140 × 55 mm

## Replaceable Nozzles (mm)

PCB-1	PCB-2
Membrane type air pump	Batten's air pump
5 cores line	Silicone tube
21-10130 handle cover	21-10130 handle under cover
Power line	LED display
4 cores heating element	21-10130 whole handle set
With a sheath 2-core heating element	-

תיאור פריט: משטח חימום לפירוק והלחמת רכיבי SMD 540W

יצרן: TENMA

דגם: 21-10135

מק"ט טלמיר: 4362602

מיקום באתר: מלחמים וציוד הלחמה / מלחמים ותחנות הלחמה / תחנות הלחמה

יבואן: טלמיר אלקטרוניקה בע"מ