

Multimeter Digital



| Basic Functions | Range | Best Accuracy |
|--|---|---------------|
| DC Voltage | 400 mV / 4 V / 40 V / 300 V | ± (0.8% + 1) |
| AC Voltage | 4 V / 40 V / 300 V | ± (1.2% + 3) |
| Resistance | 400 Ω / 4 kΩ / 40 kΩ / 400 kΩ / 4 MΩ / 40 MΩ | ± (1% + 2) |
| Capacitance | 4 nF / 40 nF / 400 nF / 4 μF / 40 μF / 200 μF | ± (4% + 3) |
| Frequency | 10 Hz / 100 kHz | ± (0.5% + 3) |
| Special Functions | | |
| Auto ranging | ✓ | |
| Duty cycle | 0.1% to 99.9% | |
| Diode | ✓ | |
| Continuity buzzer | ✓ | |
| Relative mode | ✓ | |
| Data hold | ✓ | |
| Full icon display | ✓ | |
| Sleep mode | ✓ | |
| Low battery display | ✓ | |
| Input impedance for DC voltage measurement | Around 10 MΩ | |
| Maximum display | 3999 | |

תיאור פריט: רב מודד כיס דיגיטלי 72-7935 POCKET SERIES

יצרן: TENMA

דגם: 72-7935

מק"ט טלמיר: 7463819

מיקום באתר: ציוד בדיקה ומכשירי מדידה / רבי מודדים וצבתות זרם / רבי מודדים MULRIMETERS
יבואן: טלמיר אלקטרוניקה בע"מ

Multimeter Digital



General Characteristics

| | |
|-----------------------------|--|
| Power | 3 V battery (CR2032) |
| LCD size | 43 × 22 mm |
| Product colour | Orange and grey |
| Product net weight | 62 g |
| Product size | 58 × 108 × 12 mm |
| Standard accessories | Test lead, battery, English manual, vinyl holder |
| Standard individual packing | Blister |

Part Number Table

| Description | Part Number |
|-----------------------------|-------------|
| Multimeter, Digital, Pocket | 72-7935 |

תיאור פריט: רב מודד כיס דיגיטלי 72-7935 SERIES POCKET

יצרן: TENMA

דגם: 72-7935

מק"ט טלמיר: 7463819

מיקום באתר: ציוד בדיקה ומכשירי מדידה / רבי מודדים וצבתות זרם / רבי מודדים MULRIMETERS

יבואן: טלמיר אלקטרוניקה בע"מ