


# Digital Storage Oscilloscope



## Features:

Channels	4	
Bandwidth	300MHz	
Sample Range	2GS/s	
Rise Time	≤1.2ns	
Memory Depth	24kpts	
Vertical Sensitivity	2mV/div to 5V/div	
Time Based Range	1ns to 50s/div	
Storage	Setup, Wave, Bitmap, CSV	
Trigger Type	Edge, Pulse, Video, Slope, Alternate	
Interfaces	USB Device, USB, Host, Multimeter interface	
<b>Basic Functions</b>	<b>Range</b>	<b>Best Accuracy</b>
DC Voltage	400mV/4V/40V/400V	±(1%+5)
AC Voltage	4V/40V/400V	±(1.2%+5)
DC Current	4mA/40mA/400mA/4A	±(1%+5)
Resistance	400Ω/4kΩ/400kΩ/4MΩ/40MΩ	±(1.5%+5)
Display Count		4,000
Auto Range		√

## General Characteristic:

Power	100 - 240V AC, 45Hz - 440Hz
LCD Size	5.7 inches 64k Colour TFT LCD(320 × 240)
Product Colour	White and Grey
Product Net Weight	3.8kg
Product Size	330mm × 165mm × 165mm
Standard Accessories	Probe × 2 (1x, 10x switchable), Power Cord USB Cable, PC Software
Standard Individual Packing	Gift Box English Manual

## Part Number Table

Description	Part Number
Digital Storage Oscilloscope, 300MHz	72-7630

תיאור פריט: אוסילוסקופ שולחני דיגיטלי – 4 ערוצים – 300MHZ

יצרן: TENMA

דגם: 72-7630

מק"ט טלמיר: 4760542

מיקום באתר: ציוד בדיקה ומכשירי מדידה / אוסילוסקופים / אוסילוסקופים שולחניים

יבואן: טלמיר אלקטרוניקה בע"מ

