

Handheld Oscilloscope



Specifications

| Feature | |
|---------------------------------|---|
| Bandwidth | 60 MHz |
| Rise time | ≤ 5.8 ns |
| Real-time sampling rate | 250 MS/s |
| Equivalent sampling range | 25 GS/s |
| Vertical sensitivity | 5 mV to 50 V / div |
| Record length (Maximum) | 2 × 512 k |
| Scan time base | 5 ns to 50 s / div |
| Trigger type | Edge, pulse, video and alternate |
| Automatic waveform measurements | 27 |
| Frequency counter | 6 digits frequency counter |
| Ports | USB Host |
| Mathematics | Add, subtract, multiply, divide, FFT |
| Interface | Colour and mono display selectable |
| Power | The provided battery or out-sourced adaptor |
| Life of Battery | 3 hrs |
| Other Features | Multimeter, special LCD copy feature |
| Multimeter | |
| Resistance | 600 Ω / 6 MΩ / 60 MΩ : ± (1.5% + 5 digits) |
| | 6 kΩ / 60 kΩ / 600 kΩ : ± (1.2% + 5 digits) |
| DC Voltage | 600 mV, 6 V, 60 V, 600 V, 1,000 V : ± (1% + 5 digits) |
| AC Voltage | 600 mV, 6 V, 60 V, 600 V, 700 V : |
| (45 Hz to 400 Hz) | ± (1.2% + 5 digits), Frequency : < 200 Hz |
| - | ± (1.5% + 5 digits), Frequency : ≥ 200 Hz |

Handheld Oscilloscope



Specifications

| Multimeter | |
|---------------------------------|--|
| DC Current | 6 mA, 60 mA, 600 mA : ± (1.2% + 5 digits) |
| | 6 A : ± (1.5% + 5 digits) |
| AC Current (45 Hz to 400 Hz) | 6 mA, 60 mA, 600 mA : ± (2% + 5 digits) |
| | 6 A : ± (2.5% + 5 digits) |
| Capacitance | 6 nF, 6 mF : ± (5% + 10 digits) |
| | 60 nF, 600 nF, 6 μF, 60 μF, 600 μF : ± (1.5% + 5 digits) |
| Continuity buzzer | ✓ |
| Diode | |
| Trend diagram | |
| Testing mode | Manual / auto ranging |
| Maximum display | 5,999 |

General Characteristics

| | |
|------------------------------|--|
| Power | 230 V ac (UK + Euro power adaptor) |
| LCD size | Diagonal 145 mm (5.7 inches) |
| Product colour | Grey + White |
| Product net weight | 1.8 kg |
| Product size | 268 × 168 × 60 mm |
| Accessories | Probe × 2 (1×, 10× switchable) |
| | Current voltage convertor × 2 (UT-M03, UT-M04) |
| | Power cord, DC adaptor and English manual, test lead |
| Standard individual packing | Tool and gift box |
| Standard quantity per carton | 4 pieces |
| Standard carton measurement | 475 × 460 × 380 mm (0.1 CBM per export carton) |
| Standard carton gross weight | Around 23.2 kg |

Specifications and other information are subject to change without further notice

Part Number Table

| Description | Part Number |
|---|-------------|
| Oscilloscope, Handheld DSO, 2CH, 60 MHZ | 72-9355 |

תיאור פריט: אוסילוסקופ ידני דיגיטלי – 2 ערוצים – 60MHZ

יצרן: TENMA

דגם: 72-9355

מק"ט טלמיר: 5281602

מיקום באתר: ציוד בדיקה ומכשירי מדידה / אוסילוסקופים / אוסילוסקופים ידניים

יבואן: טלמיר אלקטרוניקה בע"מ

