





- ROBUST** : Metal case, epoxy finish.
- PRECISE** : Good long-term stability.
 - 1% resistors.
- EASY** : front panel.
 - Intermediate tap at each decade.



ROBUSTS
RESISTANCE from
0,1 Ohm to
11,111 111 MOhms



Specifications

- The DR04-07 boxes use metal film resistors offering 0.5% accuracy and a temperature coefficient of 50 ppm/°C.
- The DR08 box use thick film resistors offering 1% accuracy and a temperature coefficient of 100 ppm/°C
- Output of each decade on 4mm safety socket.
- Screen outputs (front panel and case) on safety earth socket.
- Robust switches with metal frame and gold-plated contacts. (R < 6mΩ and R < 9mΩ for DR08).• Max power rating : 0.5 W.

Other specifications

- Safety : Complies with EN 61010-1, DR04-07, overvoltage category I, pollution degree 1. DR08, overvoltage category III, pollution degree 1.
- Max voltage : DR04-07, 150V AC/DC (reinforced insulation). 250V AC/DC with earth connected to safety earth socket (single insulation). DR08, 300V AC/DC (reinforced insulation)
- Presentation : aluminium mounting plate, screen-printed satin epoxy finish, metal case, epoxy finish.

Type	Weight Kg	Decades	Multiplier in OHMS							Totale Resistance
			1	10	100	1K	10K	100K	1M	
DR 04	1	4		•	•	•	•			11,110 KΩ
DR 05	1,4	5		•	•	•	•	•		111,110 KΩ
DR 06	1,44	6		•	•	•	•	•	•	1 111,110 KΩ
DR 07	1,52	7		•	•	•	•	•	•	11,111 110 MΩ
DR 08	1,4	8	•	•	•	•	•	•	•	11,111 111 MΩ
Accuracy %			3	1	1	1	1	1	1	
Max current			2.3A	700 mA	200mA	70mA	20mA	7mA	2 mA	0,7 mA

- The assembly is mounted on the front panel which fits into a 19" standard subrack.
- Mounting plate dimensions :

DR04 : H = 2U (U = 44.45 mm) - L = 84F (F = 5.08 mm)
DR 05, 06, 07 : H = 2U (U = 44.5 mm) - L = 84F (F = 5.08 mm)

