



Eco Version

High Output Version

Audible Signals - Industrial ECO TLM AUDIBLE MODULES

Industrial LED-TLM Eco Tower Light > Audible Modules

Product overview

These audible modules have been designed for use in conjunction with the Moflash LED-TLM Eco Tower Light Module range. They are a simple fix addition that offers an audible warning signal in addition to the multiple visual ones that the tower offers.

The module can be pre-set with either a pulsed or continuous tone. The Eco buzzers have been designed for local indication only but a higher decibel output version (Ac only) is available.

This has two dB outputs selectable by a slide switch inside the enclosure.

Features



- Continuously rated
- Low current consumption
- Cost effective audible solution
- Quick & easy installation or upgrade

Material

Black ABS Plastic



ECO TLM-AUD-02 >

Code No:	LED-TLM-AUD-02
Voltage:	24v Dc ---
Operating Temperature:	-25 to +55 °C
Current:	55mA
Pulsed Tone Rate:	60/80 (time/min)
Output dB:	100
IP Protection:	IP65






ECO TLM-AUD-04 >

Code No:	LED-TLM-AUD-04
Voltage:	85-275v Ac ~
Operating Temperature:	-25 to +55 °C
Current:	<55mA
Output dB:	80
IP Protection:	IP54



HIGH OUTPUT TLM-AUD120-04 >

Code No:	LED-TLM-AUD120-04
Voltage:	85-275v Ac ~
Operating Temperature:	-25 to +55 °C
Current:	<20
Output dB:	100-120 selectable
IP Protection:	IP65



APPROVALS and
CONFORMITIES

