

Tapes



Features:

- Good gap-filling between slightly uneven materials
- Very high adhesion to most common materials
- Tested by FIRA for the application of mirror mounting
- Suggested tape coverage 40cm²/Kg of mirror (BS 7449,1991)
- Good tack copes well with difficult surfaces and conditions
- High shear and foam strength for mounting and holding
- Good long term ageing and resistance to water
- Outstandingly reliable general purpose product

A strong white closed cell PE foam coated on both sides with a high performance rubber based adhesive giving very high tack while retaining high shear

Limitations

Limited resistance to solvents, plasticisers, UV light and high temperatures

Technical Details

Thickness	: 0.9 mm
Peel Adhesion at 23°C	: 25* N / 25 mm
Peel Adhesion at 70°C	: N / 25 mm
Shear (AFERA) at 23°C	: 120 N / 625 mm ²
Shear (PSTQ at 23°C	: 1,000 hrs
Temperature Range	: -40 to +60°C
Minimum Application Temperature	: +10°C
* Foam Tears	

Availability

HSHT 0.8 is also available in black
Roll widths from 6 mm to 1,350 mm
Roll lengths normally 50 m or 100 m; for other lengths please enquire
Pads, sheets and die-cut shapes

Part Number Table

Description	Part Number
Tape, 2 Sided, Foam, 25 MM, PK25	HSHT STRIP 0.8X25X150
Tape, 2 Sided, Foam, 25 MM	HSHT ROLL 0.8X25MMX5M
Tape, 2 Sided, Foam, Precut	HSHT PADS 0.8X12X25MM
Tape, 2 Sided, Foam, Precut	HSHT PADS 0.8X25X25MM