

Encoder Control DC Power Supply

Single Channel, 0-30V, 0-10A

TENMA™


Features:

- Input voltage : 230V
- Complete digital control / programmable
- 10mV / 1mA resolution
- Low noise and ripple
- CV / CC constant voltage and constant current modes
- Settable OCP and OVP, constant protection mode
- 5 sets of parameters can be stored and recalled
- Output switch control
- Power-off memory function
- Keyboard lock function to prevent operator errors
- Easy alternative to the traditional digital-display power supplies
- Certified by CE

**RoHS
Compliant**

Specifications:

Voltage Range / Current Range	0-30V / 0-10A
Load Regulation	Voltage : $\leq 0.01\% + 2\text{mV}$ / Current : $\leq 0.1\% + 5\text{mA}$
Line Regulation	Voltage : $\leq 0.01\% + 3\text{mV}$ / Current : $\leq 0.1\% + 3\text{mA}$
Setup Resolution	Voltage : 10mV / Current : 1mA
Setting accuracy (25°C $\pm 5^\circ\text{C}$)	Voltage : $\leq 0.5\% + 20\text{mV}$ / Electric current : $\leq 0.5\% + 5\text{mA}$
Ripple (20hz - 20M)	Voltage : $\leq 2\text{mVrms}$ / Electric current : $\leq 5\text{mA}_{\text{rms}}$
Temperature Coefficient	Voltage : $\leq 100\text{ppm} + 10\text{mV}$ / Current : $\leq 100\text{ppm} + 5\text{mA}$
Read Back Accuracy	Voltage : 10mV / Current : 1mA
Read Back Temperature Coefficient	Voltage : $\leq 100\text{ppm} + 10\text{mV}$ / Current : $\leq 100\text{ppm} + 5\text{mA}$
Reaction Time (10% Rated load)	Voltage : $\leq 100\text{mS}$ / Current : $\leq 100\text{mS}$
Operation Environment	Indoor use Altitude: $\leq 2,000\text{m}$ Ambient temperature 0 ~ 40°C Relative humidity $\leq 80\%$
Interfaces	Optional Interfaces (for programmable models only) : RS232, USB
Accessories	User manual, Power cord (1.2M), USB cord (1.2M; for programmable models only)
Weight and Dimension	7kg / 110mm(W) $\times$ 156mm(H) $\times$ 310mm(D)
Storage Environment	Ambient temperature -10°C to +70°C Relative humidity : $\leq 70\%$

Part Number Table

Description	Part Number
Encoder Control DC Power Supply, Single Channel, 0-30V, 0-10A	72-2925

TENMA™

תיאור פריט: ספק כוח מעבדתי – 0-30V / 0-10A , PROG , 72-2925

יצרן: TENMA

מיקום באתר: ציוד בדיקה ומכשירי מדידה / ספקי כוח מעבדתיים / ספקי כוח מעבדתיים – יציאה אחת
יבואן: טלמיר אלקטרוניקה בע"מ