

Mini Clamp Meter

TENMA™


General Characteristics

Power	: AAA 1.5V × 2
LCD Size	: 39.3mm × 26.5mm
Product Colour	: Orange and Grey
Product Net Weight	: 170g
Product Size	: 175mm × 60mm × 33.5mm
Standard Accessories	: Batteries, Test Lead

Specifications:

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/600V	±(0.7%+3)
AC Voltage	2V/20V/200V/600V	±(1%+3)
AC Current	2A/20A/100A	±(2.5%+5)
DC Current	2A/20A/100A	±(2%+3)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1%+2)
Capacitance	2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(4%+5)
Special Functions		
Display Count		2000
Auto Range		√
Jaw Capacity		17mm
True RMS		√
Diode	Around 3V	√
V.F.C.		√
NCV		√
Data Hold		√
Zero Mode		√
LCD Backlight		√
Auto Power Off	Around 15 Minutes	√
Continuity Buzzer		√
Low Battery Indication		√
Input Protection		√
Input Impedance for DCV	≥10MΩ	√

Part Number Table

Description	Part Number
Mini Clamp Meter	72-2985

TENMA™

תיאור פריט: צבת אמפרמטר דיגיטלי – 72-2985

יצרן: TENMA

 מיקום באתר: ציוד בדיקה ומכשירי מדידה / רבי מודדים וצבתות זרם / רבי מודדים צבת
 יבואן: טלמיר אלקטרוניקה בע"מ