
































ERSADUR long-life soldering tip series 832, 842 and 852

Lead-free
Bleifrei
SAFE 

- ANALOG 60/60 A
- ANALOG 80/80 A
- DIGITAL 80 A
- DIGITAL 2000 A with POWER TOOL soldering iron
- ELS 8000/M/D

- ERSA 15+ / 25+ / 35+
- MICRO-CON 60 iA with POWER TOOL soldering iron
- MS 6000 / MS 8000/D
- MULTI-PRO
- MULTI-SPRINT

- MULTI-TC
- RDS 80
- TWIN 80 A with ERGO TOOL

0832UD/UDLF  pencil point, 0.4 mm Ø, extended	0832SD/SDLF  pencil point, 0.8 mm Ø, extended	0832BD/BDLF  pencil point, 1.0 mm Ø	0832YD/YDLF  chisel-shaped, 1.6 mm
0832CD/CDLF  chisel-shaped, 2.2 mm	0832KD/KDLF  chisel-shaped, 2.2 mm, extended	0832ED/EDLF  chisel-shaped, 3.2 mm	0832VD/VDLF  chisel-shaped, 5.0 mm
0832FDLF  angled face, 2.0 mm	0832TDLF  angled face, 3.0 mm Ø	0832NDLF  angled face, 4.0 mm Ø	0832PW  PowerWell with concave portion
0832HD  SolderWell with concave portion, bent	0832AD  PLCC blade, 1.5 mm	0852OD  PLCC blade, 2.0 mm	0832WD  chisel-shaped, 2.5 mm, bent
0832RD  chisel-shaped, 5.0 mm, bent	0832GDLF  angled face, 14 mm, 35°	0832LDLF  angled face, 17 mm, 35°	0832MDLF  angled face on both sides, 8 mm
0842UD/UDLF  pencil point, 0.4 mm Ø, extended	0842SD/SDLF  pencil point, 0.8 mm Ø, extended	0842BD/BDLF  pencil point, 1.0 mm Ø	0842YD/YDLF  chisel-shaped, 1.6 mm
0842CD/CDLF  chisel-shaped, 2.2 mm	0842KD/KDLF  chisel-shaped, 2.2 mm, extended	0842ED/EDLF  chisel-shaped, 3.2 mm	0842ID  pencil point, 0.4 mm Ø, bent
0842JD  chisel-shaped, 2.2 mm, bent	0852GD  angled face, 8.0 mm	0852VD  chisel-shaped, 5.0 mm	