

ERSADUR pairs of desoldering tips, series 422/452

- DIGITAL 2000 A with CHIP TOOL
- MICRO-CON 60 iA with SMD DESOLDERING PINCETTE 40
- REWORK 80
- SMD 8000

- SMT UNIT 60 AC/A with CHIP TOOL/
SMD DESOLDERING PINCETTE 40
- all i-CON stations with CHIP TOOL



0452FDLF040 4 mm, for e.g. SO 8 GT/14 GT/16GT	0422ED 6 mm, for e.g. SOIC 8	0452EDLF060 6 mm, for e.g. SOIC 8	0452FDLF075 7.5 mm, for e.g. SOIC 2/SOT 23
0452FDLF100 10 mm, for e.g. SOIC 16	0452FDLF125 12.5 mm, for e.g. SOIC 20	0452FDLF150 15 mm, for e.g. SOIC 24	0452FDLF175 17.5 mm, for e.g. SOIC 28
0452FDLF200 20 mm, for e.g. SOIC 32	0452FDLF250 25 mm, for e.g. SOIC 40	0452FDLF275 27.5 mm, for components of 27.5 mm side length	0452FDLF400 40 mm, for components of 40 mm side length
0452QDLF100 90°, length 10 mm, for e.g. PLCC 20	0452QDLF125 90°, length 12.5 mm, for e.g. PLCC 28	0452QDLF150 90°, length 15 mm, for e.g. QFP, TQFP and TTQFP 80T25	0452QDLF175 90°, length 17.5 mm, for e.g. PLCC 44
0452QDLF200 90°, length 20 mm, for e.g. PLCC 52	0452QDLF250 90°, length 25 mm, for e.g. PLCC 68	0452RDLF150 length 15 x 12.5 mm, for e.g. PLCC 32	0452RDLF225 length 22.5 x 16.5 mm, for e.g. QFP 100
0422MD ellipse, for MELF and MINIMELF	0452MDLF020 ellipse, for MELF and MINIMELF	0422SD for MICROMELF	*Please note: Tips 0422SD must be used in combination with the tip turn protection set to ensure good results. Tip turn protection set for TC 40 desoldering tweezers and DESOL- DERING PINCETTE 40 on request.

Hot-air nozzle series 472

- i-CON VARIO 2
with i-TOOL AIR S hot-air iron
- i-CON VARIO 4
with i-TOOL AIR S hot-air iron



0472AR hot-air nozzle, 2 mm ø	0472BR hot-air nozzle, 4 mm ø	0472CR hot-air nozzle, 6 mm ø	0472DR hot-air nozzle, bent, 1.7 mm / 0.067 in ø	0472ER hot-air nozzle, bent, 3.5 mm / 0.138 in ø
---	---	---	--	--