

# Neodymium shallow pot datasheet

## Hook Magnet

- Zinc plated body
- 80° max operating temp
- Used in point of sale etc.



### Product Information

| Product Number | Diameter<br>mm | Thickness*<br>mm | Overall Height Inc. Hook<br>mm | Thread<br>mm | Weight<br>g | Pull Force<br>kg | Units / Pack |
|----------------|----------------|------------------|--------------------------------|--------------|-------------|------------------|--------------|
| E1030/NEO      | 10             | 4.5              | 15                             | M3           | 4.5         | 2.5              | 20           |
| E1031/NEO      | 13             | 4.5              | 15                             | M3           | 7.5         | 6                | 20           |
| E1032/NEO      | 16             | 4.5              | 20.5                           | M4           | 13.2        | 9.5              | 20           |
| E1033/NEO      | 20             | 6                | 22                             | M4           | 16.5        | 14               | 10           |
| E1034/NEO      | 25             | 7                | 23                             | M4           | 34          | 20               | 10           |
| E1035/NEO      | 32             | 7                | 30                             | M5           | 48          | 35               | 5            |

If you have any more questions, require technical assistance and would like a quotation, simply contact us.

[www.eclipsemagnetics.com](http://www.eclipsemagnetics.com)

Eclipse Magnetics Ltd, Atlas Way, Sheffield, S4 7QQ, England  
T +44 (0)114 225 0600 F +44 (0)114 225 0525 E [info@eclipsemagnetics.com](mailto:info@eclipsemagnetics.com)

While every effort has been made to ensure the accuracy of the information in this publication please note that specifications may change without notice.

