



Cordless shrub and grass shear set

Isio

An indispensable garden tool: the Isio multifunctional tool, the perfect aid for your daily gardening tasks.

[Go to product](#)



Key product features

- Multifunctional: the Isio is more versatile than ever before thanks to a new range of “Multi-click” attachments.
- Compact and lightweight: the ideal shape, size and weight for effortless operation.
- High endurance and power: lithium-ion battery and “Anti-Blocking System” enable undisturbed work for up to 50 minutes with one battery charge.

Other product advantages

- Charge level indicator. Four-stage LED indicator that displays the charging state
- “Anti-Blocking System”. Prevents the shear from stalling and enables relaxed work without interruptions
- Compact and ergonomic design for optimum handling and more comfort
- Easy changing of the attachments thanks to SDS System
- Lithium-ion technology: short charge times, no self-discharge, no memory effect and always ready to use. Delivers up to 50 minutes runtime

Comes complete with

- Charger
- Multi-Click edging shear blade 8 cm (F 016 800 326)
- Multi-Click shrub shear blade 12 cm (F 016 800 327)

Part number: 0600833172

EAN code: 3165140630757



Cordless shrub and grass shear set

Isio

Technical data

Battery type: Lithium-ion

Battery voltage: 3,6 V

Battery capacity: 1,5 Ah

Battery runtime: up to 50 mins

Battery charge time: 3,5 h

Blade length: 12 cm (shrub)

Blade width: 8 cm (grass)

Tooth spacing: 0,8 cm

Weight: 550 g

Noise / vibration information

Measured values determined according to EN 60335
Total vibration values (vector sum of three directions).

grass shear

Vibration emission value ah: 2.5 m/s²

Uncertainty K: 1.5 m/s²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 70 dB(A); Sound power level dB(A). Uncertainty K= dB.

Measured values determined according to EN 60745
Total vibration values (vector sum of three directions).

shrub shear

Vibration emission value ah: 2.5 m/s²

Uncertainty K: 1.5 m/s²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 58 dB(A); Sound power level 79 dB(A). Uncertainty K= 3 dB.



Functions

3.6 Volt

“Anti-Blocking System”

SDS system

Charge level indicator