



DCH333X2

54V XR Flex Volt SDS Plus Hammer

FEATURES

- Brushless motor with high capacity XR FLEXVOLT 9.0Ah 18V/54V Lithium-ion battery platform for extreme runtime and reduced maintenance
- Category-leading high speed drilling performance at more than 66 holes (18mm Ø x 80mm) per charge
- Rotation stop mode for light chiseling in plaster, tiles and render and impact stop mode for rotary only drilling in wood and metal
- Perform & Protect: best-in-class vibration at 8.5m/s², minimizing user fatigue
- Bright white LED with delay feature improves visibility Ideal for drilling anchors and fixing holes into concrete, brick and masonry from 4mm to 30mm
- Compact, lightweight and ergonomic design for improved comfort and support during extended operating periods

SPECIFICATIONS

Impact energy (EPTA 05/2009)	3.5 J
No Load Speed	0-1000 rpm
Blows per Minute	0-4480 bpm
Max. Drilling Capacity [Concrete]	30 mm
Max. Drilling Capacity [Wood]	30 mm
Max. Drilling Capacity [Metal]	13 mm
Weight	3.7 kg
Length	400 mm
Height	250 mm
Width	95 mm
Hand/Arm Vibration - Hammer drilling into concrete	7.5 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Hand/Arm Vibration – Chiselling	8.5 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Hand/Arm Vibration - Drilling into metal	<2.5 m/s ²
Uncertainty K 3 (Vibration)	1.5 m/s ²
Hand/Arm Vibration - Screw driving without impact	<2.5 m/s ²
Uncertainty K 4 (Vibration)	1.5 m/s ²
Sound Pressure	94 dB (A)
Sound Pressure Uncertainty	3 dB (A)
Sound Power	105 dB (A)
Sound Power Uncertainty	3 dB (A)