

Product information

18v LXT Combi Drill



DHP482RFWJ

Capacity in Steel	13 mm
Capacity in Wood	38 mm
Chuck Capacity	1.5 - 13 mm
Capacity in Masonry	13 mm
Blows per Minute (Hi) - ipm	0 - 28,500 ipm
Blows per Minute (Lo) - ipm	0 - 9,000 ipm
No Load Speed (Hi)	0 - 1,900 rpm
No Load Speed (Lo)	0 - 600 rpm
Voltage	18 v
Torque Settings	21 + drill
Battery Type	Lithium-ion
Battery Quantity (3.0 Ah)	2
Vibration K factor	1.5 m/sec ²
Noise sound pressure	82 dB(A)
Noise sound power	93 dB(A)
Noise K factor	3 dB(A)
Net weight	1.5 - 1.8 kg
Max. Fastening Torque (Soft Joint)	36 Nm
Max. Fastening Torque (Hard Joint)	62 Nm
Vibration: Impact drilling into concrete	6.0 m/sec ²
Vibration: Drilling into metal	2.5 m/sec ²



LITHIUM-ION

STANDARD EQUIPMENT: 194204-5 BATTERY BL1830 18V Li-ion, 821550-0 MAKPAC CONNECTOR CASE (TYPE 2), 837916-4 MAKPAC INLAY FOT TYPE 2 CASE, DC18RC DC18RC COMPACT CHARGER

- Electric brake
- 2 mechanical gears.
- Variable speed control by trigger
- Forward/reverse rotation
- Twin LED job light
- Ergonomic soft grip
- Keyless Chuck
- Compact and lightweight design
- Equipped with Battery protection circuit: designed to protect the battery from damages due to overdischarge, high temperature or overload current.
- Metal gears

Details correct as of: 23-5-2018

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makitauk.com