



- CHARGER 1-4 CELL LITHIUM MAX. 2A CHARGE CURRENT 1-10 CELL NIMH MAX. 2A CHARGE CURRENT 3/6 CELL LEAD ACID MAX. 2A CHARGE CURRENT
- Using our own designed software a customized configuration (charge current, cut-off voltage, etc) is quickly available
- Wide range input 100-240V / 50-60Hz
- Traveller system with different country version mains plugs available for UK, Euro, US, Australia as well as IEC320
- Approvals for US UL1310 / Australia / FCC
- Electronic protection against short circuit and reverse polarity
- Secondary plugs with variable configuration
- High stock levels in Europe mean quick deliveries
- Small quantities of customized solutions are also possible
- Other configurations available on request
- Part no. 2000-0001-00

Battery Type	Number of Cells	Battery Voltage	Max. Charge Current	Software Part No.
Lithium	18	3.7V	1500mA	0185-0023
	18	3.7V	2000mA	0185-0001
	2S	7.4V	1300mA	0185-0022
	28	7.4V	2000mA	0185-0002
	38	11.1V	700mA	0185-0025
	3S	11.1V	2000mA	0185-0003
	4S	14.8V	600mA	0185-0024
	4S	14.8V	1200mA	0185-0026
	4S	14.8V	2000mA	0185-0004
NiMH/NiCd	1-10	1.2-12V	2000mA	0185-0011
Lead Acid	3	6V	2000mA	0185-0009
	6	12V	2000mA	0185-0010