

This drawing may not be used, reproduced or made available in any form without written or prior written approval. The supplier acknowledges that, with the acceptance of this drawing, he is a participant in manufacturing the illustrated part in accordance with the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements.

This drawing may not be used, reproduced or made available in any form without written or prior written approval. The supplier acknowledges that, with the acceptance of this drawing, he is a participant in manufacturing the illustrated part in accordance with the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements. The supplier is not responsible for any deviations from the drawing's requirements.

Technische Daten/
technical data : Akku/
battery
Chemie/
chemistry : Li-Ion
Zellenzahl/
no. of cells : 1 Zelle/ cell 18650 LG B4
Kapazität/
capacity : nom. 2600mAh discharge at 0.2C
min. 2500mAh discharge at 0.2C
to:20°C; EV(Discharge End Voltage): 2.75V per cell

Innenwiderstand/
impedance : < 100m0hm (battery and safetyboard)
Nominalspannung/
nominal voltage : 3.7V
Standard Ladespannung/
standard charge voltage : 4.2V±1%
Standard Entladespannung/
standard discharge voltage : 2.75V per cell
Nominaler Ladestrom/
nominal charge current : 0.5C
Maximaler Ladestrom/
maximum charge current : 2500mA (limited by safetyboard)
Ladeendstrom/
charge end current : 0.01C recommended
Maximaler Entladestrom/
maximum discharge current : 2500mA (limited by safetyboard)
Anwendungstemperaturbereich/
ambient temperature range : 0°C...+45°C charge
-20°C...+60°C discharge
-20°C...+30°C storage max. 1 year
-20°C...+45°C storage max. 3months

Selbstentladung/
self discharge : ≤ 5% / month at20°C
≤ 10% / month at30°C
≤ 20% / month at40°C

Standards/ : UN 3480, Subsection 38.3
All cells and batterypacks type tested according
to UN manual of test and criteria subsection 38.3

Technische Daten/
technical data : Sicherheitsschaltung/
safety board

Überladeschutzspannung/
over charge voltage detection : 4.325V±50mV

Wiedereinschaltspannung/
over charge release voltage : 4.15V±50mV

Entladeabschaltspannung/
over discharge detection voltage : 2.5V±100mV

Wiedereinschaltspannung/
over discharge release voltage : 3V±100mV

Nominaler Lade/Entladestrom/
nominal operating current : 2.5A

Entlade Abschaltstrom/
discharge cut off current : 5A±1A

Kurzschlusschutz/
short circuit protection : gegen äußeren Kurzschluss/
against external short circuit

Temperaturschalter/
temperature switch : ---

MOSFET : in Masse
in Gnd

Rückstellkriterium/
release condition : Last trennen, Aktiv nach Anladen/
cut load, release after charging up

Nettogewicht/
net weight : 47.5g

Leiterplattenmaterial/
pcb material : FR4

Standards : CE

