

Technical drawing of the ANSMANN HST-1000 battery pack, showing front and back views with dimensions and labels.

Dimensions:

- Overall width: 112
- Overall height: 116

Front View (Left):

- Brand name: **ANSMANN**
- Charging status indicators:
 - charging (solid bar)
 - ready (dashed bar)
 - error (dashed bar)
- Terminal color labels:
 - silber/silver (pointing to the top terminal)
 - blau/blue (pointing to the bottom terminal)

Back View (Right):

- Terminal color label:
 - blau/blue (pointing to the bottom terminal)
- Technical specifications:
 - Input: 15VDC (min. 36W)
 - Output: **HIGH SPEED** **FAST**
 - AA: 4400mAh
 - AAA: 1100mAh
 - 2200mAh
 - 550mAh
 - CE mark
 - Read instructions before use!

Labels and Markings:

- Hohlsteckerbuchse/ hollow plug socket
- Ø2,1xØ5,5mm
- Polarität/polarity

Gewicht/ : 750g inkl. Zubehör und Verpackung/
weight : 750g incl. accessories and package
Verpackung/ : Einzelverpackung, blisterverpackt ca.172x74x252mm (LxBxH)
packaging : inkl. mehrsprachiger Bedienungsanleitung VE: 4 Stück/
individual packaging, blisterpacked approx.172x74x252mm (LxWxH)
incl. multilingual operating instructions PU: 4 pieces

Diagram of the back of the device showing the battery compartment. The compartment is circular with a latch at the top. Inside, there are four circular battery slots arranged in a square pattern. Below the slots, there is a table of input and output specifications, a USB symbol, and a CE mark.

Input: 15VDC (min. 36W)	
Output: HIGH SPEED	FAST
AA 4400mA	2200mA
AAA 1100mA	550mA

Read Instructions before use!

4x Duo LED rot-grün/
4x Duo LED red-green

inkl. 4x NiMH 2850mAh Minion AA

Schalter blau/switch blue

inkl. 4x NiMH
2850mAh Mignon AA
DIGITAL Akkus/
rechargeable batteries

\ Schalter blau/switch blue

Hohlstecker/
hollow-plug
ø2,1xø5,5x10mm

H03VWH2-F 2x0,75mm²
schwarz 1,8m lang/
black 1,8m long

Euro Netzleitung/
Euro mains cord

Euro – UK Adapter
10950063/01

Technische Daten Steckernetzgerät/ technical data plug-in power supply	
Eingangsspannung/ input voltage	: 100–240VAC $\pm 10\%$ 50/60Hz
Nenn-Ausgangsspannung/ nominal output voltage	: 15VDC $\pm 10\%$
Ausgangsstrom/ output current	: 2400mA
Anzeige/ indicator	: Power LED rot/red
Betriebstemperatur/ operating temperature	: $-10^{\circ}\text{C}.....+25^{\circ}\text{C}$
Lagertemperatur/ storage temperature	: $-25^{\circ}\text{C}.....+70^{\circ}\text{C}$
Gewicht/ weight	: 200g
Gehäuse/ case	: Steckergehäuse schwarz 110x59x36mm (LxBxH)/ plug-in case black 110x59x36mm (LxWxH)
Gehäusematerial/ housing material	: UL94V-0
Approbation/ certification	: CE ; GS ; cETLus ; SAA

Rundkabel schwarz 1,8m $\pm$ 10cm lang/
roundcable black 1.8m $\pm$ 10cm long

SWITCHING AC POWER SUPPLY
FOR DIGISPEED 4 ULTRA+
MODEL: MW7M25SE
INPUT: 100-240V~
50/60Hz
820mA MAX
OUTPUT: 15V ---2.4A 36W

FOR OFFICE EQUIPMENT USE ONLY

 LISTED IN US
3009785

 A/10363EA



 

MADE IN CHINA

80 ± 5

ferrite core

Verwendungsbereich/Application range für Anfrage/for inquiry AN17804N				Zul. Abweichung/ Allowable deviation	Oberfläche/ Surface	Maßstab/Scale 1:1	Gewicht/Weight
						Werkstoff/Work material, Modell-Nr.	
				2008	Datum/Date	Name	Zeichnungsname/Drawing name Tischladegerät/desktop charger DIGI SPEED 4 Ultra+/2850 UK
				Erstellt/ Drawn by	31.07.	KA	
V0	---	31.07.08	KA			Zeichnungsnummer/Drawing number Artikelnummer/Part number	Blatt / Sheet
Version	Anderung/Change	Datum/Date	Name	Ursprung/Origin	Proj. 047/35/06	Ersatz für/Replaced by	Ersatz durch/Replacement through
						5707153/UK	1