

Polyurethane Resin



Description

RoHS **Compliant**

This is a two-part, optically clear polyurethane resin formulated for potting and encapsulation. The cured resin system is semi-rigid and durable. This is suited to LED applications.

Typical Properties

Liquid Properties

Base Material : Polyurethane : 1.03g/ml Density Part A - Resin Density Part B - Hardener : 1.12g/ml

Part A Viscosity : 700mPa s @ 23°C Part B Viscosity : 1200mPa s @ 23°C Mixed System Viscosity : 900mPa s @ 23°C

Mix Ratio (Weight) : 1.27 : 1 : 1.44 : 1 Mix Ratio (Volume) Usable Life (20°C) : 17 mins Gel Time (23°C) : 21 mins Cure Time (23°C) : 24 hours Colour Part A - Resin : Clear Colour Part B - Hardener : Clear Shrinkage : < 1%

Exotherm (Measured on 100ml sample in a

Cylinder of diameter 49.4mm @ 23°C) : < 90°C

Cured System

Thermal Conductivity : 0.2W/m.K **Cured Density** : 1.08g/ml : -40°C to +120°C Temperature Range

Max Temperature Range (Short Term (°C)/30mins)

(Application and Geometry Dependent) : +130 Dielectric Strength : 11kV/mm Volume Resistivity : 10¹⁴ Ω-cm : A75 Shore Hardness @ 25°C Colour (Mixed System) : Colourless Refractive Index : 1.488 Flame Retardancy : No Permittivity @ 50 Hz

10 days @ 20°C/1 hour @ 100°C : 0.7%/1.4%

Water Absorption (9.7mm thick disk, 51mm diameter)

General Properties

Packaging : 250g Resin Pack Shelf Life : 12 months

Storage : Dry Conditions: Above 15°C, Below 35°C

: Meets UL94 V-0 **UL** Approval







sales@talmir.co.il דוא"ל:



Polyurethane Resin



Mixing

When in Resin pack form, the resin and hardener are mixed by removing the clip and moving the contents around inside the pack until thoroughly mixed. To remove the clip, remove both end caps, grip each end of the pack and pull apart gently. By using the removed clip, take special care to push unmixed material from the corners of the pack. Mixing normally takes from two to four minutes depending on the skill of the operator and the size of the pack. Both the resin and hardener are evacuated prior to packing so the system is ready for use immediately after mixing. The corner may be cut from the pack so that it may be used as a simple dispenser.

Part Number Table

Description	Part Number
Polyurethane Resin, Optically Clear, 250g, Pack	MC002570



