

Heat Shrink Tubings

pro-POWER



Features:

- Semi-rigid, adhesive lined, polyolefin tubing
- Splash-resistant, moisture-resistant covering
- Rugged protection against abrasion, vibration and flexing
- Excellent strain relief and insulation of weak points

Specifications:

Material	: Polyolefin
Colour	: Black
Shrink ratio	: 3.1
Shrink temperature	: 110°C
Maximum operating temperature	: 125°C
Minimum operating temperature	: -55°C
Reel length (metric)	: 1.2 m

Specification Table

Fully Shrunk Diameter	Unshrunk Diameter	Wall Fully Recovered Thickness	Part Number
1	3.2	0.95	HS114 1.2M
1.6	4.8	1.1	HS115 1.2M
2.2	6.4	1.2	HS116 1.2M
2.7	7.9	1.3	HS117 1.2M
3.2	9.5	1.4	HS118 1.2M
4.2	12.7	1.5	HS119 1.2M
5.2	15	1.8	HS120 1.2M
6.3	19.1	2	HS121 1.2M
8.5	25.4	2.1	HS122 1.2M
10.2	30	2.2	HS123 1.2M
13.5	39	2.4	HS124 1.2M
17	50	2.7	HS125 1.2M

Dimensions : Millimetres

pro-POWER