

Model Specification

Motor (230v ~ 50/60 Hz):	650W
Impact Energy:	1.6J
Speed Range:	0-1100min ⁻¹
Machine Weight:	3.5kg
Product Dimensions (HxWxD):	210mm x 320mm x 85mm
Recommended Maximum Duty Cycle:	30mins
Max. Drill Diameter (Steel):	13mm
Max. Drill Diameter (Concrete):	20mm
Max. Drill Diameter (Wood):	30mm
Sound Pressure Level (Under Load):	Lpa = 88.6dB(A) Lwa = 99.6dB(A) K = 3dB(A)
Vibration:	1.5m/s ²

Packaging

Gross Weight:	4.7kg
Packaging Weight:	1.2kg
Packaging Dimensions (HxWxL):	310mm x 125mm x 380mm

Standard Equipment

Supplied With Machine: 3 x SDS Drill Bits (6 x 160mm, 8 x 160mm, 10 x 160mm), 2 x Chisel Bits (160mm Flat Chisel & 160mm Pointed Chisel), Depth Stop, Moulded Carry Case, Operator's Manual.



Pallet Configuration

Total Number per pallet (2m High):

126 (6 high x 21)

Machine Barcodes (EAN13)

SDS4-800 110v (UK):

0000000000000

SDS4-800 230v (UK):

0000000000000

SDS4-800 230v (EU):

0000000000000

Container Quantity

20' - 0" Container:

1700 pieces

40' - 0" Container:

3400 pieces

40' - 0" HQ Container:

3850 pieces

Product Overview

With four functions (Drill, Chisel, Rotation & Hammer) and high impact energy of 1.6 Joules the SDS4-800 is versatile and very effective.

The variable speed feature allows for optimum control and the hi-torque 650W motor packs the punch required to drill into tough applications, such as steel, concrete & other masonry.

Other features include an adjustable auxiliary handle making it easy to direct into position, as well as an ergonomic main handle with soft grips for comfort.

It's light and portable without losing the key attributes of strength and robustness; ideal for daily and extensive use.

