

Mini Anemometer



Specifications

LCD Display	Dual line, 4-digit LCD
Sensor type	NTC
Operating Temperature	0 to 50°C (32°F to 122°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Operating Humidity	<80%RH
Storage Humidity	<80%RH
Bluetooth	Yes
Max / Min / AVG	Yes
Data Hold	Yes
Backlight	Yes
Low Battery Indicated	Yes
Auto Power Off	Yes
Disable Auto Power Off	Yes

Air Velocity	Range	Resolution	Accuracy
m/s (meter per second)	1.1 - 25m/s	0.01m/s	±(3% + 0.3m/s)
km/h (kilometers per hour)	4 - 90km/h	0.1km/h	±(3% + 1km/hr)
ft/min (feet per minute)	220 - 4920ft/min	1ft/min	±(3% + 40ft/m)
mph (miles per hour)	2.5 - 56mph	0.1mph	±(3% + 0.4mph)
Knots (nautical mph)	2.2 to 48 knots	0.1 knots	±(3% + 0.4 knots)
Air Temperature °C / °F	Range	Resolution	Accuracy
	-10°C to 60°C (14°F to 140°F)	0.1°C / 0.1°F	±2°C (4°F)

Part Number Table

Description	Part Number
Mini Anemometer with Bluetooth	ST-90

