

## Stacking 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC

**TENMA**™



### Specifications

Lead Length	: 500mm/19.7" 1m / 3.3ft
Connector Type A	: Stacking 4mm Shrouded Banana Plug
Connector Type B	: Stacking 4mm Shrouded Banana Plug
Voltage Rating	: CAT II 1000V
Current Rating	: 36A
Resistance	: 500mm: 15mΩ 1m: 20mΩ
Cable	: 2.5mm <sup>2</sup> , PVC
Contact Material	: Brass and Beryllium Copper, Nickel Plated
Insulator Material	: Polypropylene
Insulator Colour	: White, Blue, Brown, Grey, Yellow, Black, Red, Green, Yellow/Green and Purple
Temperature	: -20°C to 80°C

### Applications

General purpose electric and electronic testing, controlling and measuring.

### Part Number Table

Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	White	500mm	72-14096
	Blue		72-14098
	Brown		72-14100
	Grey		72-14102
	Yellow		72-14104
	Black		72-14106
	Red		72-14108
	Green		72-14112
	Blue	1m	72-14078
	Brown		72-14080

**TENMA**™

## Stacking 4mm Banana Plug to Plug Safety Patchcord - 2.5mm<sup>2</sup> PVC



Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 2.5mm <sup>2</sup> PVC, 1000V, 36A	Grey	1m	72-14082
	Yellow		72-14084
	Yellow/Green		72-14086
	Black		72-14088
	Red		72-14090
	Green		72-14092
	Purple		72-14094

