





GH-DP 3730 Dirty water pump

Powerful and robust dirt water pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 30 mm in size. The pump is equipped with a float switch for automatic ON/OFF – operation for a varying water level. High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application.

Features

- Handle (1)
- Float switch (2)
- Universal connection for 25 mm (1") and 32 mm (1¼") male thread hose connection as well as G1 (ca. 33.3 mm) male thread
- 90 ° angel bracket G1½ (ca. 47.8 mm) male thread x G1½ (ca. 47.8 mm) male thread (3)

GH-DP 3730

Cable reel (4)

High quality floating ring seal (5)

Technical Data

Mains: 230 V ~ 50 Hz
Power: 370 W
Delivery capacity max.: 9,000 l/h
Delivery height max.: 5 m
Immersion depth: 5 m

Water temperature max.: 35 °C

Hose connection: G1½ (ca. 47.8 mm)Female thread

Foreign particle size up to:
Mains cable:
ON function:
OFF function:
Exhaust height:
Ø 30 mm
10 m H05RN-F
approx. 50 cm
approx. 5 cm
approx. 40 mm

Product weight: 4.3 kg

Logistic Data

2


Net weight: 4.4 kgGross weight: 4.8 kg


Packing dimensions: 220 x 180 x 400 mmBar Code: 4006825 587203

Sales Unit: 4 pcs

Performance data:







PVC-drainage hose 10 m/1" Einhell Grey Art.-No.: 41.737.14 Bar code: 4006825 549249

3

