





GH-DP 7835 Dirty water pump

Powerful and robust dirt water pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 35 mm in size. The pump is equipped with a float switch for automatic ON/OFF – operation for a varying water level. High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application.

Features

- Handle (1)
- Float switch (2)
- Universal connection for 25 mm (1") and 32 mm (11/4") male thread hose connection as well as
 G1 (ca. 33.3 mm) male thread
- 90 ° angel bracket G1½ (ca. 47.8 mm) male thread x G1½ (ca. 47.8 mm) male thread (3)

GH-DP 7835

- Cable reel (4)
- High quality floating ring seal (5)

Technical Data

Mains: 230 V ~ 50 Hz
Power: 780 W
Delivery capacity max.: 15,700 l/h
Delivery height max.: 8 m

Immersion depth: 8 mWater temperature max.: 35 °C

Hose connection: G1½ (ca. 47.8 mm) Female thread

Foreign particle size up to:

Mains cable:

ON function:

OFF function:

Exhaust height:

Ø 35 mm

H05RN-F

approx. 50 cm

approx. 5 cm

approx. 40 mm

Product weight: 5.0 kg

Logistic Data

2


Net weight:Gross weight:5.1 kg5.6 kg

Packing dimensions: 220 x 180 x 390 mm
 Bar Code: 4006825 587210


Sales Unit: 4 pcs

Performance data:









PVC-drainage hose 10 m/1" Einhell Grey

Art.-No.: 41.737.14

Bar code: 4006825 549249