

SPANNFIX VICES



with dissipative surface

BERNSTEIN clamping vices SPANNFIX constructed on ball-and-socket joints are rotatable easily in all directions and capable of being set securely with maximum working capacity by simple operation. A set screw below the ball socket allows an individual adjusting of the ball power. Long life is guaranteed by highest black powder-coated aluminium casting and surface-refined steel-parts. With a surface resistance between 10^7 and $10^8 \Omega$ the ESD types ensure a safe dissipation of static charges.

9-205 ESD BERNSTEIN

SPANNFIX screw-on vice with dissipative surface

for work benches or laboratory tables
with max. table thickness of 80 mm

Technical data:

Clamping pressure	150 kp
Clamping capacity	70 mm
Clamping depth	38 mm
Jaw width	50 mm

interchangeable plastic jaws from
dissipative material - Art.-No. 9-206-50 ESD

Weight: 1.450 kg

9-251 ESD Universal clamp base with dissipative surface

with ball joint and threaded stud M 12 x 1.5, for work benches
or laboratory tables with max. table thickness of 80 mm

Weight: 0.950 kg

9-252 ESD Screw-on mounting vice with dissipative surface

Technical data: see 9-205 ESD

Weight: 0.560 kg

9-253 ESD Circuit board holder

adjustable from 25 mm to 270 mm clamping capacity, correct setting by
adjusting the centre position, firm clamping of the printed circuit by built-in
resilience in the locating arms, height of locating arms 70 mm

Weight: 0.280 kg

9-255 ESD Angular adapter with dissipative surface

to permit a larger turning circle when using 9-253

Gewicht: 0.095 kg

9-256 Clamping lid for circuit boards with components

covered with 20 mm thick ESD foam

Components of different sizes are pressed in such a way that soldering can
be carried out correctly after the circuit board holder has been turned.

Size of cover: 240 x 130 mm

Use: in conjunction with circuit board holder 9-253

Weight: 0.260 kg

9-257 ESD Rapid turning device with dissipative surface

with permanently connected angular adapter, permits swift rotation of the
circuit board holder with the PCB and clamping lid through 180° .

Weight: 0.270 kg



9-205 ESD



9-251 ESD



9-252 ESD



9-253 ESD



9-255 ESD



9-256



9-257 ESD