
Product data sheet





Cordless Combi

GSB 18V-21 Professional



Reliable and powerful entry model to the 18 V professional cordless drill driver segment

The most important data

<u> </u>	
Battery voltage	18 V
Max. drilling diameter in masonry	10 mm
Max. screw diameter	10 mm

Part number: 0 601 9H1 102

> More product information

Technical Data

Performance data

Torque, max. (hard/soft)	55 / 21 Nm
No-load speed (1st gear / 2nd gear)	0 - 480 / 0 - 1.800 rpm
Battery type	Lithium-ion
Chuck capacity, min./max.	1,5 / 13 mm
Torque settings	20+1
Battery and power	
Battery voltage	18 V
Size and weight	
Weight excl. battery	1.2 kg
Drilling diameter	
Max. drilling diameter in wood	35 mm
Max. drilling diameter in steel	10 mm
Max. drilling diameter in masonry	10 mm
Screw diameter	
Max. screw diameter	10 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	3,3 m/s ²
Uncertainty K	1,5 m/s ²
Impact drilling in masonry	
Vibration emission value ah	6,7 m/s ²
Uncertainty K	1,5 m/s ²
Screwdriving	
Vibration emission value ah	1,0 m/s ²
Uncertainty K	1,5 m/s ²
Noise	
Sound pressure level	82 dB(A)
Sound power level	93 dB(A)
Uncertainty K	3 dB

Invented for life

Product data sheet

Power tools for trade & industry

Advantages

- Professional performance: Sufficient performance and runtime for the main applications due to 55 Nm hard
- Professional quality: Reliable, durable drill driver for daily usage thanks to full metal gear and electronic cell protection (ECP).
- Professional design: Designed for professional applications thanks to 13 mm keyless chuck



























