

# Retrofit Braid

pro-POWER



## Features:

- Flexible
- Wrap around - side entry
- Zero halogen
- High resistance to abrasion
- Fluid and chemical resistant
- Operating temperature : -50°C to 150°C
- Tensile strength : 650 N / m<sup>2</sup>
- Flammability : ASTM D 2671

Retrofit is a woven PET wrap around sleeve designed for protecting wire harnesses and cables. The spring wrap action enables application after termination of wires and cables. Installation is efficient as breakouts are quickly produced during harnesses building

## Specification Table

| Description                          | Nominal Inner Diameter (mm) | Length (m) | Part Number       |
|--------------------------------------|-----------------------------|------------|-------------------|
| Braid, Retrofit, Black, 5 mm, 100 m  | 50                          | 100        | KPT WRAP 5MM BLK  |
| Braid, Retrofit, Black, 10 mm, 100 m | 10                          |            | KPT WRAP 10MM BLK |
| Braid, Retrofit, Black, 13 mm, 50 m  | 13                          | 50         | KPT WRAP 13MM BLK |
| Braid, Retrofit, Black, 19 mm, 25 m  | 19                          | 50         | KPT WRAP 19MM BLK |
| Braid, Retrofit, Black, 25 mm, 25 m  | 25                          |            | KPT WRAP 25MM BLK |
| Braid, Retrofit, Black, 30 mm, 25 m  | 30                          |            | KPT WRAP 30MM BLK |
| Braid, Retrofit, Black, 38 mm, 25 m  | 38                          |            | KPT WRAP 38MM BLK |
| Braid, Retrofit, Black, 50 mm, 25 m  | 50                          |            | KPT WRAP 50MM BLK |

pro-POWER