


*Now you're connected!*

### About Amphenol Commercial Products

Amphenol's commercial connector products are used in a variety of end user applications including networking, telecom, server & computer, storage & HDD, consumer electronics and entertainment, professional audio & Industrial & Military/Aerospace.

### Related Products

#### RJSSE




P/N RJSSE-5081 SHOWN  
SINGLE PORT, 8 POSITION,  
WITH SHIELD AND LIGHT PIPE

#### RJSAE



P/N RJSAE-5385-02 SHOWN  
STACKED 2x1, 8 POSITION,  
WITH SHIELD AND LEDs



P/N RJHSE-3081 SHOWN  
SINGLE PORT VERTICAL MOUNT,  
NO SHIELD, WITH LEDs

P/N RJHSE-5385-02 SHOWN  
TWO PORT REGULAR MOUNT,  
WITH SHIELD AND LEDs

P/N RJHSE-G080-04 SHOWN  
FOUR PORT REGULAR MOUNT,  
NO SHIELD OR LEDs

### Overview

This product specification defines the general use and performance parameters for Amphenol's RJHSE series of inverted modular jacks.

Availability: Single, multiport, vertical and right angle connectors with a wide variety of LED and shielding options.

### Usage

The RJHSE inverted modular jacks with superior EMI performance supports Ethernet Protocols. Shielding available for increased EMI performance and LEDs for Link Activity and Network Speed verification.

### Applications

Intended for use in applications such as:

#### Networking & Telecom

- Wireless (WiMAX)
- Network servers
- Hubs, routers, switches

#### Office & Home Equipment

- PC's, Laptops, Copiers/Printers
- Telephones, modems
- Surge Protectors
- ATMs, Vending Machines

#### Consumer Goods

- Security Systems
- Set Top Boxes
- Video Game Systems

#### Miscellaneous

- Multi-Media Equipment
- Industrial Equipment
- POS Terminals

# Now you're connected!

## About Amphenol Commercial Products

Amphenol's commercial connector products are used in a variety of end user applications including networking, telecom, server & computer, storage & HDD, consumer electronics and entertainment, professional audio & Industrial & Military/Aerospace.

## Related Products

### RJSSE



P/N RJSSE-5081 SHOWN  
SINGLE PORT, 8 POSITION,  
WITH SHIELD AND LIGHT PIPE

### RJSAE



P/N RJSAE-5385-02 SHOWN  
STACKED 2x1, 8 POSITION,  
WITH SHIELD AND LEDs

## Electrical Characteristics

Contact resistance:	20 mΩ max.
Insulation resistance:	500 MΩ minimum at 500V DC for 2 minutes max.
Current rating:	1.5 Amps
Voltage rating:	125 Volts AC
DWV	1000 VAC, 60 Hz. 1 min.
LED forward DC current:	20mA typical
LED forward Voltage:	1.9 Volts max. @ 2mA (for single colors) 2.6 Volts max. @ 20mA (for Bi-colors)
LED reverse voltage:	5 Volts minimum
LED light intensity:	0.4 to 1.5 mcd @ 2mA (for single colors) 0.5 mcd min. @ 2mA (for Bi-colors)
LED wave length:	Yellow: 587± 7 nm measured @ 20mA Green: 565± 6 nm measured @ 20mA Red: 625± 5 nm measured @ 20mA

## Mechanical Characteristics

Mating connector insertion force: 5.0 lbs. Maximum.  
Mating connector pull retention force: 20 lbs Minimum.  
Durability: 750 mating & unmating cycles  
Recommended soldering temperature: Wave soldering peaked at 260° C for 5 seconds maximum.  
Connectors without LED's are suitable for IR Reflow

Operating temperature: -55° C to +85° C

## Material Requirements

RJHSE connectors are RoHS compliant.  
Unless otherwise specified, the materials for each component shall be:

### Insulator:

- High Temp thermoplastic. Complies with UL 94V-0, Black color

### Contacts:

- Phosphor Bronze hard temper with gold thickness options (6μ", 15μ", 30μ", 50μ") over 50μ" minimum Nickel on contact mating area.
- 100μ" minimum matte tin plating on soldering tail

### Shield:

- Stainless Steel with tin dipped tails

### LED:

- Tin plating on LED tails

## Available Documents

### Drawing Numbers:

P-RJHSE-5XXX-XXX	8 Position Modular Jack, optional LEDs and Shielding, 1, 2, 4, 5, 6 and 8 port versions
P-RJHSE-7XXX-XXX	6 Position Modular Jack, Optional LEDs and Shielding, 1, 2 and 4 port versions
P-RJHSE-3XXX-XXX	Vertical Mount, Single Port Modular Jack, Optional LEDs and Shielding
P-RJHSE-LXXX-XXX	Low Profile Modular Jack, Optional LEDs and Shielding, 1 and 2 port versions

Contact factory or Authorized Amphenol representative for additional configurations

Amphenol Canada Corp.  
605 Milner Avenue  
Toronto, Ontario, Canada, M1B 5X6  
+1 416 291 4401

www.amphenolcanada.com

Copyright © Amphenol Corporation 2011 • All rights reserved

Page 2 of 2

# Amphenol