


Screened FTP Cat 7A LSZH Cable

1,200MHz

pro-POWER

RoHS
Compliant


Application:

Horizontal Wiring in LAN

Multi-Construction

: 4 Pair

Cable Construction

Conductor	: Solid Bare Copper
Conductor Area CSA	: 0.32mm ²
Wire Size AWG	: 22
Construction	: 0.62 ±0.01
Standard Dia.(mm)	: 0.62
Insulation	: Skin - Foam - Skin
Average Thickness	: 0.4
Insulation Dia.(mm)	: 1.45 ±0.1 × 2C Twist
Al-Pet shield(on each pair, Al outward)	: ≥115%
Braiding Shield	: Tin-Plated Copper Wire
Construction	: 0.12 ±0.003 × 8 × 6

Jacket

Jacket Material	: Low Smoke Zero Halogen (LSZH) Flame Retardant Polyethylene
Thickness(mm)	: 0.7
Dia.(mm)	: 8.2 ±0.3
Jacket Colour	: Blue

Colour

Insulation colour are	: Blue, White/Blue Orange, White/Orange Green, White/Green Brown, White/Brown
------------------------------	--

Characteristics

Max. Conductor DC Resistance at 20°C (Ω/Km)	: <66.6
Rated Temperature(°C)	: 70
Velocity ratio	: 78%
Impedance(Ω)	: 1-100MHz 100 ±15 100-250MHz 100 ±20 250-500MHz 100 ±25 500-1,000MHz 100 ±30 1,000-1,200MHz 100 ±32

pro-POWER

Screened FTP Cat 7A LSZH Cable


1,200MHz

pro-POWER

Performance:

Frequency (MHz)	Attenuation (dB)	NEXT (dB)	PS NEXT (dB)	Return loss (dB)	ELFEXT (dB)	PSELFEXT (dB)
1	2.1	78	75	20	78	75
4	3.7	78	75	23	78	75
10	5.8	78	75	25	75.3	72.3
16	7.3	78	75	25	71.2	68.2
31.25	10.3	78	75	23.6	65.4	62.4
62.5	14.6	78	75	21.5	59.4	56.4
100	18.5	75.4	72.4	20.1	55.3	52.3
250	29.7	69.4	66.4	17.3	47.3	44.3
500	42.8	64.9	61.9	17.3	41.3	38.3
600	47.1	63.7	60.7	17.3	39.7	36.7
900	58.5	61.1	58.1	15.5	36.2	33.2
1,000	61.9	60.4	57.4	15.1	35.3	32.3
1,200	68.4	59.2	56.2	14.3	33.7	30.7

Design:



pro-POWER