

Wiha Professional-Bit.

Wiha Professional Bits - everything but standard.

Style E 6.3 (1/4").



7040 Z Professional bit, slotted, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.

Order-No.	⌀	↔	⊖	↔
33961	2.5	70	0.4	5
01790	3.0	50	0.5	5
33962	3.0	70	0.5	5
01792	3.5	50	0.6	5
33963	3.5	70	0.6	5
01791	4.0	50	0.5	5
01794	4.0	50	0.8	5
33964	4.0	70	0.8	5
01793	4.5	50	0.6	5
01795	5.5	50	0.8	5
01796	5.5	50	1.0	5
33965	5.5	70	1.0	5
01798	6.5	50	1.2	5
33966	6.5	70	1.2	5
01799	8.0	50	1.2	5
01800	8.0	50	1.6	5



7041 Z Professional bit, Phillips, style E 6.3.
Extra: Overlength bits available in lengths of 50, 70, 90, 110, 127 and 150 mm.

Order-No.	⊕	↔	↔
31960	PH00	50	5
31961	PH00	70	5
31962	PH00	90	5
32105	PH0	50	5
35456	PH0	70	5
35457	PH0	90	5
33703	PH1	50	5
01803	PH1	70	5
04126	PH1	90	5
23213	PH1	110	5
23219	PH1	127	5
22509	PH1	150	5
33704	PH2	50	5
01805	PH2	70	5
04009	PH2	90	5
05800	PH2	110	5
06888	PH2	127	5
22510	PH2	150	5
33705	PH3	50	5
04010	PH3	70	5
04127	PH3	90	5
23215	PH3	110	5
23217	PH3	127	5
22511	PH3	150	5

Style E 6.3 (1/4").



7049XH Professional bit, Xeno-slotted/Phillips, style E 6.3.
For terminal screws (slotted/ Phillips).
Application: For fastening and unfastening positive/ negative screws in switchboard systems, fuse boxes, terminal blocks and relays.

Order-No.	⊕	↔	↔
32490	SL/PH1	50	5
32491	SL/PH1	70	5
32686	SL/PH1	90	5
32492	SL/PH2	50	5
32493	SL/PH2	70	5
32687	SL/PH2	90	5



7042 Z Professional bit, Pozidriv, style E 6.3.
Extra: Overlength bits available in lengths of 50, 70, 90, 110, 127 and 150 mm.

Order-No.	⊕	↔	↔
31957	PZ0	50	5
31958	PZ0	70	5
31959	PZ0	90	5
33706	PZ1	50	5
01808	PZ1	70	5
01809	PZ1	90	5
23221	PZ1	110	5
23225	PZ1	127	5
23227	PZ1	150	5
33707	PZ2	50	5
01811	PZ2	70	5
01812	PZ2	90	5
05799	PZ2	110	5
06889	PZ2	127	5
23228	PZ2	150	5
33708	PZ3	50	5
04059	PZ3	70	5
04176	PZ3	90	5
23223	PZ3	110	5
23226	PZ3	127	5
22512	PZ3	150	5



7049XZ Professional bit, Xeno-slotted/Pozidriv, style E 6.3.
For terminal screws (slotted/ Pozidriv).
Application: For fastening and unfastening positive/ negative screws in switchboard systems, fuse boxes, terminal blocks and relays.

Order-No.	⊕	↔	↔
32494	SL/PZ1	50	5
32495	SL/PZ1	70	5
32688	SL/PZ1	90	5
32496	SL/PZ2	50	5
32497	SL/PZ2	70	5
32689	SL/PZ2	90	5

Style E 6.3 (1/4").



7045R Professional bit, TORX® with MagicSpring®, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
Extra: MagicSpring® made of stainless steel holds TORX® screws tight at various angles.
Attention: Screw must not be attached to the rotating bit.

Order-No.	⊗	↔	↔
34452	T10	50	5
34453	T15	50	5
34454	T20	50	5
34455	T25	50	5
34456	T30	50	5
34457	T40	50	5

Style E 6.3 (1/4").



7045BE Professional bit, TORX® ball end, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all internal TORX® screws, especially in hard-to-reach places.
Extra: The TORX® ball end enables fastening and unfastening at an angle of up to 25°. With elongated TORX® profile behind ball end.

Order-No.	⊗	↔	↔
32409	T9	50	5
32410	T10	50	5
32416	T10	70	5
32417	T15	50	5
32418	T15	70	5
32411	T20	50	5
32419	T20	70	5
32420	T20	90	5
32412	T25	50	5
32421	T25	70	5
32422	T25	90	5
32413	T27	50	5
32414	T30	50	5
32423	T30	70	5
32424	T30	90	5
32415	T40	50	5



7045BE 9570 Professional bits TORX® ball end in compact bit band, 10-pcs.
Blister packed.
Bits: 70 mm Standard bits.
Application: Extra long bits for all types of fastening in trade and industry.
Extra: Compact plastic bit band with belt clip.

Order-No.	Series	↔
32804	7045BE 9570	1
⊗	7045BE	2xT10 2xT15 2xT20 2xT25 2xT30

Wiha Professional-Bit.

Wiha Professional Bits - everything but standard.

Style E 6.3 (1/4").



7045 Z Professional bit, TORX®, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
Extra: Overlength bits in lengths of 50, 70, 90, 110 and 150 mm.

Order-No.	⌘	↔	▬
32299	T5	50	5
32302	T6	50	5
33709	T6	70	5
33717	T6	90	5
32303	T7	50	5
33710	T7	70	5
33718	T7	90	5
32304	T8	50	5
33711	T8	70	5
33719	T8	90	5
32305	T9	50	5
33712	T9	70	5
33720	T9	90	5
32306	T10	50	5
33713	T10	70	5
33721	T10	90	5
33725	T10	110	5
33726	T10	150	5
32307	T15	50	5
33714	T15	70	5
33722	T15	90	5
33727	T15	110	5
33728	T15	150	5
32308	T20	50	5
33715	T20	70	5
33723	T20	90	5
33729	T20	110	5
33730	T20	150	5
32309	T25	50	5
33716	T25	70	5
33724	T25	90	5
33731	T25	110	5
33732	T25	150	5
33920	T27	50	5
33921	T27	70	5
33922	T27	90	5
33923	T30	50	5
33924	T30	70	5
33925	T30	90	5
33926	T30	110	5
33927	T30	150	5
33928	T40	50	5
33929	T40	70	5
33930	T40	90	5
33931	T40	110	5
33932	T40	150	5

Style E 6.3 (1/4").



7045 Z TR Professional bit, TORX® H, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
Extra: Hole in the bit tip for TORX® Tamper Resistant security screws.

Order-No.	⌘	↔	▬
21045	T7H	50	5
21047	T8H	50	5
20218	T9H	50	5
20219	T10H	50	5
24867	T15H	50	5
20220	T20H	50	5
20221	T25H	50	5
20222	T27H	50	5
20223	T30H	50	5
20224	T40H	50	5



7046 Z Professional bit, TORX PLUS®, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
Extra: Reinforced profile cross-section transfers approx. 25% more torque than with a TORX® profile.

Order-No.	⌘	↔	▬
28481	5IP	50	5
26000	6IP	50	5
26002	7IP	50	5
23195	8IP	50	5
23197	9IP	50	5
23199	10IP	50	5
23201	15IP	50	5
23203	20IP	50	5
23205	25IP	50	5
23207	27IP	50	5
23209	30IP	50	5
23211	40IP	50	5



7048 Z Professional bit, Robertson, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
Extra: A tapered tip allows for easy insertion of the bit into the screw.

Order-No.	⌘	↔	▬
06637	1	50	5
06638	2	50	5
06639	3	50	5

Style E 6.3 (1/4").



7047R Z Professional bit, hexagon ball end, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
To insert and remove screws from holes or cavities, specially in difficult to access areas.
Extra: MagicRing® made from spring steel holds all standard screws in every position. Ball end allows a working angle up to 25°.

Order-No.	⌘	↔	▬
25739	3.0	50	5
25740	4.0	50	5
25741	5.0	50	5
25742	6.0	50	5



7043R Z Professional bit, hexagon, style E 6.3.
Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.
To insert and remove screws from holes or cavities.
Extra: MagicRing® made from spring steel holds all standard screws in every position.

Order-No.	⌘	↔	▬
23145	3.0	50	5
23147	4.0	50	5
23149	5.0	50	5
23151	6.0	50	5

Style E 6.3 (1/4").



7043 Z Professional bit, hexagon, style E 6.3.

Order-No.	⌘	↔	▬
05301	1.5	50	5
05302	2.0	50	5
34554	2.0	70	5
05303	2.5	50	5
34555	2.5	70	5
04194	3.0	50	5
34556	3.0	70	5
04195	4.0	50	5
34557	4.0	70	5
04196	5.0	50	5
34558	5.0	70	5
04197	6.0	50	5
34559	6.0	70	5
04198	8.0	50	5
34560	8.0	70	5



NEW
7041 VB1 Single bits display, 90 mm bits.
Acrylic glass display with 70 pieces.

Order-No.				
36162	Acrylic glass display with 70 pieces.			
⊕	7041 Z	5xPH1	5xPH2	5xPH3
⊕	7042 Z	5xPZ1	5xPZ2	5xPZ3
⊗	7045 Z	5xT10	5xT15	5xT20
		5xT25	5xT30	5xT40
○	7143	5x1/4	5x1/4	

NEW
7041 VB2 Single bits display, 150 mm bits.
Acrylic glass display with 70 pieces.

Order-No.				
36163	Acrylic glass display with 70 pieces.			
⊙	7143	5x1/4	5x1/4	
⊕	7041 Z	5xPH1	5xPH2	5xPH3
⊕	7042 Z	5xPZ1	5xPZ2	5xPZ3
⊗	7045 Z	5xT10	5xT15	5xT20
		5xT25	5xT30	5xT40

Wiha Info



Wiha MagicRing®:
spring steel ring
reliably holds hex screws
in place.