


Spacer

DURATOOL



Features:

- Material Designation : 101(+)(f1), 101F(+)(f1), 101L(+)(f1), E101(+)(f1), E101L(f1), 132F(+)(f1), 135F(+)(f1)
- Product Description : Polyamide 6.6 (PA6.6), designated "zytel" furnished as pallets
- Dielectric Strength : 13kV/mm
- Volume Resistivity : 14 ($10^k \Omega\text{-cm}$)
- CTI : 0
- HVTR : 0
- D495 : 6
- Overall Length : 2mm
- External Dia : 6.3mm
- External Length / Height : 2mm

Specification Table:

Colour	Minimum Thickness (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
All	0.71	V-2	4	0	130	75	85	725	960
	1.5		3					750	
	3		2					800	
	6							-	


(+) Virgin and regrind up to 50% by weight inclusive, have the same basic material characteristics.

(f1) Suitable for outdoor use with respect to exposure to ultraviolet light and water exposure.

DURATOOL

Spacer

DURATOOL



Dimensions : Millimetres

Part Number Table

Description	Part Number
PCB Round Spacer, Nylon 6.6, Natural	D01480

DURATOOL