



Slotted for torque screwdriver with long handle

28590

Order-No.				mm	mm	max. Nm	
26227	0,25	1,5	4	175	42	0,15	10
26228	0,4	2,0	4	175	42	0,4	10
26151	0,4	2,5	4	175	42	0,4	10
26277	0,5	3,0	4	175	42	0,6	10
26278	0,6	3,5	4	175	42	1,1	10
26279	0,8	4,0	4	175	42	2,5	10

Blade tip DIN ISO 2380-1.

Phillips for torque screwdriver with long handle

28591

Order-No.				mm	mm	max. Nm	
26199	PH000	4	175	42	0,4	10	
26196	PH00	4	175	42	0,4	10	
26197	PH0	4	175	42	0,9	10	
26058	PH1	4	175	42	3,8	10	
27079	PH2	4	175	42	5,5	10	

Blade tip DIN ISO 8764-1.

Pozidriv for torque screwdriver with long handle

28592

Order-No.				mm	mm	max. Nm	
26198	PZ0	4	175	42	0,9	10	
26148	PZ1	4	175	42	3,8	10	
26889	PZ2	4	175	42	5,5	10	

Blade tip DIN ISO 8764-1.

TORX® MagicSpring® for torque screwdriver with long handle

28595R

Order-No.				mm	mm	max. Nm	
27818	T6	4	175	42	0,6	10	
27812	T7	4	175	42	0,9	10	
27813	T8	4	175	42	1,3	10	
27814	T9	4	175	42	2,5	10	
27815	T10	4	175	42	3,8	10	
27816	T15	4	175	42	5,5	10	
27817	T20	4	175	42	8,0	10	
29467	T25	4	175	42	8,0	10	

TORX® for torque screwdriver with long handle

28595

Order-No.				mm	mm	max. Nm	
30852	T4	4	175	42	0,25	10	
26158	T5	4	175	42	0,4	10	
26064	T6	4	175	42	0,6	10	
26065	T7	4	175	42	0,9	10	
26066	T8	4	175	42	1,3	10	
26059	T9	4	175	42	2,5	10	
26067	T10	4	175	42	3,8	10	
26068	T15	4	175	42	5,5	10	
26069	T20	4	175	42	8,0	10	
26070	T25	4	175	42	8,0	10	

TORX PLUS® MagicSpring® for torque screwdriver with long handle

28596R

Order-No.				mm	mm	max. Nm	
29553	6IP	4	175	42	0,8	10	
29554	7IP	4	175	42	1,3	10	
29555	8IP	4	175	42	2,0	10	
29556	9IP	4	175	42	3,0	10	
29557	10IP	4	175	42	4,5	10	
29558	15IP	4	175	42	6,6	10	
29559	20IP	4	175	42	8,0	10	
29560	25IP	4	175	42	8,0	10	

TORX PLUS® for torque screwdriver with long handle

28596

Order-No.				mm	mm	max. Nm	
26159	5IP	4	175	42	0,5	10	
26071	6IP	4	175	42	0,8	10	
26152	7IP	4	175	42	1,3	10	
26072	8IP	4	175	42	2,0	10	
26154	9IP	4	175	42	3,0	10	
26155	10IP	4	175	42	4,5	10	
26073	15IP	4	175	42	6,6	10	
26156	20IP	4	175	42	8,0	10	
26157	25IP	4	175	42	8,0	10	

● Hexagonal ball end for torque screwdriver with long handle

28597

Order-No.	●	●	mm	mm	max. Nm	
26221	1,5	4	175	42	0,4	10
26222	2,0	4	175	42	0,9	10
26223	2,5	4	175	42	2,0	10
26224	3,0	4	175	42	3,8	10
26225	4,0	4	175	42	8,0	10

● Hexagon for torque screwdriver with long handle

28593


Order-No.	●	●	mm	mm	max. Nm	
26544	1,3	4	175	42	0,4	10
26200	1,5	4	175	42	0,9	10
26060	2,0	4	175	42	1,8	10
26061	2,5	4	175	42	3,8	10
26062	3,0	4	175	42	5,5	10
26063	4,0	4	175	42	8,0	10

INFOBOX: Ball end hex




Wiha hexagonal ball end

- The ball end can be rotated by up to 25° in both clockwise and anti-clockwise direction.



INFOBOX: MagicSpring®



Wiha TORX® MagicSpring®

- TORX® and TORX PLUS® screws are held securely in place.
- An innovation, which will benefit each user.



Cable key for circular plug connector



○ Hexagon head for torque screwdriver with long handle

28594

Order-No.	○	●	mm	mm	max. Nm	
36414	8	4	78	218	1	10
36415	9	4	78	218	1	10
36417	13	4	78	218	1,5	10
36418	14	4	78	218	1,5	10
36421	18	4	78	218	1,5	5

Adapter blade



□ internal square for torque screwdriver with long handle

285992

Order-No.	□	●	mm	
26229	1/4	4	155	10

Bit holder clamping with ball



○ for torque screwdriver with long handle

285994

Order-No.	○	●	mm	mm	
27526	1/4	4	162	11	10

Adjusting tool



for torque screwdriver with long handle

2859

Order-No.	mm	mm	
26864	146	90	1