



DESCRIPTION:

The limited fire hazard properties of this product make it ideally suited for use in special applications such as rail and aviation, public buildings and railway stations, where public safety is critical.

Low smoke, low toxicity and zero halogen, the compound meets the requirements of DIN/VDE 2007 and BS6724.

APPLICATIONS:

For protecting cable looms before and after installation.

SPECIFICATION:



COLOUR OPTIONS: Grey

MATERIAL: Nylon, Low Smoke, Halogen-Free

SERVICE TEMPERATURE RANGE: -20°C to +90°C

FLAMMABILITY: UL 15814 Rated Material

AFTER HEAT AGEING FOR 7 DAYS AT 110°C: Tensile strength 16MPa, Elongation 140%

SMOKE DENSITY: Pass ASTM E-662

STANDARDS: DIN/VDE 0207. BS 6724. Wall thickness 0.5mm

PART NUMBERS:

PART NO.	COLOUR	SIZE OD (mm)	WALL THICKNESS (mm)	LENGTH PER COIL (m)
0240	Grey	3	0.4	50
0241	Grey	6	0.6	50
0242	Grey	12	0.8	25

Other lengths are available on request, please contact us for more information.



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297