

CY LSZH Multicore Screened Control Flexible Cable

pro-POWER

RoHS
Compliant


Application:

For installation where fire, smoke emission and toxic fumes create a potential threat to life and equipment. Used as interconnecting cable for measuring, controlling or regulation in control equipment for assembly and production lines, conveyors and for computer units. Suitable for fixed installations or for flexible use when temporarily moved, and in conditions of medium mechanical stress. Can be used outdoors when protected, and in dry or damp conditions indoors.

Note: CY control cables are not suitable for fixed wiring applications requiring compliance with the regulations set out in BS7671.

Construction:

Conductor:

Class 5 flexible copper conductor according to BS EN 60228 (previously BS 6360)

Insulation:

Halogen Free Type TI6 according to BS EN 50363

Binding Tape:

PET (Polyester Tape)

Screen:

TCWB (Tinned Copper Wire Braid)

Sheath:

LSZH (Low Smoke Zero Halogen) Type TM7 according to BS EN 50363

Cable Standards

BS EN/IEC 60754-1, BS EN/IEC 60332-1-2

Characteristics:

Voltage Rating (Uo/U)

300/500V

Temperature Rating:

Installation : -15°C to +70°C

Operating : -30°C to +70°C

Minimum Bending Radius:

Fixed : 6 × overall diameter

Flexed : 15 × overall diameter

pro-POWER

CY LSZH Multicore

Screened Control Flexible Cable

pro-POWER

Core Identification:

Number Coded Cores

Black with White numbers

2 Cores Black

3 and 4 Cores to included Green/Yellow

Sheath Colour:

Grey

Dimensions:

Part Number	No. of Cores	Nominal Cross Sectional Area mm ²	Nominal Overall Diameter mm	Nominal Weight Kg/Km
PP000488	2	0.75	6.1	45
PP000489		1	6.3	57
PP000490		1.5	7.3	75
PP000491	3	0.75	6.4	63
PP000492		1	6.6	73
PP000493		1.5	7.7	95
PP000494	4	0.75	6.9	89
PP000495		1	7.1	86
PP000496		1.5	8.4	118

Conductors:

Class 5 Flexible Copper Conductors for Single Core and Multi-Core Cables

Nominal Cross Sectional Area mm ²	Maximum Resistance of Conductor at 20°C
0.75	26
1	19.5
1.5	13.3

Electrical Characteristics:

Current Carrying Capacity at 30°C

Nominal Cross Sectional Area mm ²	Current Rating Amps
0.75	12
1	15
1.5	18

pro-POWER

CY LSZH Multicore

Screened Control Flexible Cable

pro-POWER

Part Number Table

Description	No. of Cores	Reel Length	Part Number
CY LSZH Multicore Screened Control Flexible Cable	2	100m	PP000488
			PP000489
			PP000490
	3		PP000491
			PP000492
			PP000493
	4		PP000494
			PP000495
			PP000496

pro-POWER