

## Bench Top Remote Programmable Switch Mode Power Supply

**multicomp**PRO



### Description

Remote Programmable Auto Ranger SMPS with DC wave forms & Optional Ethernet Card. This multi-function constant power laboratory grade power supply is capable of generating various DC wave forms.

Application software of cyclic program, command sets, and LabVIEW Drivers are provided.

### Features

- Auto range selection with maximum 80W output
- Resolution with 10mV & 10mA with 4 digit display
- Remote programmable through USB or optional LAN card
- On housing 10 Steps list program with cycle periods running
- 3 users defined V & I panel presets for frequent use
- Master/Slave configuration for synchronization of the parallel connected output of multiple units

### Specifications

Output Voltage and Current	
Output Voltage	0.5V DC to 36V DC
Output Current	0 to 5A (Auto range with maximum output power 80W ( $V \times A \leq 80W$ ))
Constant Voltage Characteristics:	
Adjust Resolution	10mV
Load Regulation (10 – 90%)	$\leq 30mV$
Line Regulation ( $\pm 10\%$ )	$\leq 4mV$
Ripple & Noise (peak-peak)	$\leq 35mA$
Constant Current Characteristics:	
Adjust Resolution	10mA
Load Regulation (10 – 90%)	$\leq 10mA$
Line Regulation ( $\pm 10\%$ )	$\leq 10mA$
Voltmeter & Ammeter Accuracy	$\pm(0.5\% + 5 \text{ counts})$
User adjustable upper current & voltage limit	Yes

**multicomp**PRO

# Bench Top Remote Programmable Switch Mode Power Supply

**multicomp**PRO

Number of preset recalls of frequent use V&I setting	3
Remote Sensing	Yes
<b>Ramp Step Irregular Waveform functions</b>	
Number of Voltage Level Setting	10
Settable Output Time Period of each Voltage Level	0 to 1200 seconds
Remote Programmable / Control by PC	Output ON/OFF, Voltage & Current Control, Selection of Voltage and Current Preset, Programmable of cyclic output and data logging of output, Upper Voltage & Current Limit control.
Protection	Tracking Over Voltage Protection, Current Limiting Protection, Short Circuit, Overload, Over Temperature, Upper Voltage Limit, Upper Current Limit.
Standard Communication Port	USB 2.0
Optional Interface	Ethernet, Factory or User install
Additional Function	Master/Slave Control
Cooling Method	Natural Convection
Dimensions (W×H×D)	53.5mm × 127mm × 330mm / 2" × 5" × 13"
No Load Input Current at 230V AC	≤150mA
Full Load Input Current at 230V AC	≤500mA
Input Voltage Range	100V AC to 240V AC, 50Hz / 60Hz
Efficiency	≥78%
Power Factor	≥0.9
Weight	Approx. 1.9kgs / 4.2lbs

All values are based on the Standard ambient Temperature 25°C and Pressure 0.1Mpa.

## Accessories

AC Power Cord (UK / EU), Test Lead set, USB Cable, Master/ Slave Connection Cable, Terminator for Master/ Slave Connection, CDROM and Quick Start Guide

## Standard Warranty

12 Months

## Part Number Table

Description	Part Number
Programmable Switch Mode Power Supply, 5mV DC to 36V DC, 5A	MP710083

## Note:

AEN-8102 Ethernet Card is not included as standard Accessory

**multicomp**PRO