

DATA SHEET



CL150



This easy to use, stand-alone meter features an 18" flexible clamp that allows access into panels and hard to reach areas (bundled wires, awkward conductors and PLC cabinets). True RMS readings with CATIV 600V or CATIII 1000V safety ratings. Features Backlit LCD Display, Auto-power Off after 15 minutes, Max/Min, Hold, Auto-Ranging and Low Battery icons.

Specifications

Type:	Flexible AC Current Clamp	Application:	Measures AC current
Special Features:	Auto-power Off, Max/Min, Hold, Auto-Ranging and Low Battery Icons	Material:	ABS
Batteries:	2 x AAA	Auto Shut Off:	Yes
Jaw Size:	18" (457.2 mm)	Drop Protection:	6.6' (2 m)
Display:	Backlit 3000 Count	Functions:	Auto-range, Hold, Max/Min Value, Auto-power Off
Current:	0.01 to 3000A AC	Standard:	CATIV 600V, CATIII 1000V, Class 2
Included:	Carrying Case, Instruction Manual and 2 x AAA Batteries	Weight w/batteries:	6.6 oz (187 g)
Overall Length:	10.5" (266.7mm)	Overall Height:	1.06" (26.9 mm)
Overall Width:	4.12" (104.6 mm)	Weight:	5.9 oz (167 g)