



The dual display CL450 Clamp Meter is a "game changer" for the HVAC professional. This True RMS CAT IV 600V meter offers Differential Temperature, Digital Temperature Calibration, DC Micro Amp, Inrush Current, Audible Continuity, Capacitance, Diode Test, Frequency and Duty Cycle, Low-pass Filter, Low Impedance, AC and DC Current, Min/Max, AVG, Data Hold Capability. Includes carrying case, instruction manual, straight input test leads, two K-type thermocouples and 3 x AAA batteries.

Specifications

|                    |                                                |                        |                                 |
|--------------------|------------------------------------------------|------------------------|---------------------------------|
| Type:              | HVAC Clamp Meter with Differential Temperature | Application:           | HVAC                            |
| Material:          | Plastic/electronics                            | Batteries:             | 3 x AAA                         |
| Auto Shut Off:     | Yes                                            | Jaw Size:              | 2" (50.4 mm)                    |
| Drop Protection:   | 6.6 ft (2 m)                                   | Display:               | 6,000-count LCD                 |
| Voltage:           | 1000V AC; 1000V DC                             | Frequency:             | 999.9kHz                        |
| Current:           | 600A AC                                        | Capacitance:           | 6000µF                          |
| Ohms (Resistance): | 60MΩ                                           | AC Voltage:            | 1000                            |
| DC Voltage:        | 1000                                           | DC Polarity Indicator: | Y                               |
| DC Microamp:       | 200 µA with 1µA Resolution                     | Temperature Range:     | -40° to 1832°F (-40° to 1000°C) |
| Standard:          | CATIV 600V, CATIII 1000V                       | Weight w/batteries:    | 13.6 oz (386g)                  |
| Overall Length:    | 10" (254.0 mm)                                 | Overall Height:        | 1.59" (40.4 mm)                 |
| Overall Width:     | 3.77" (95.8 mm)                                | Weight:                | 12.5 oz (354 g)                 |