



# Rotary Hammer SDS+ 26mm

## HR2630

Model HR2630 is a 26mm (1") combination hammer based on predecessor model HR2610 but with improved operation mode change lever.



### TECHNICAL SPECIFICATIONS

|                                |                         |
|--------------------------------|-------------------------|
| Impact energy                  | 2.4 J                   |
| Max in concrete (TCT bit)      | 26 mm                   |
| Max in concrete (TCT core)     | 68 mm                   |
| Max in concrete (Diamond core) | 80 mm                   |
| Max in wood                    | 32 mm                   |
| Max in steel                   | 13 mm                   |
| Impacts per minute             | 0 - 4,600 ipm           |
| Input Wattage                  | 800 w                   |
| Net weight                     | 2.8 - 3.3 kg            |
| No Load Speed                  | 0 - 1200 rpm            |
| Vibration: Chiselling          | 9.5 m/sec <sup>2</sup>  |
| Vibration: Hammer Drilling     | 15.5 m/sec <sup>2</sup> |
| Noise sound pressure           | 91 dB(A)                |
| Noise K factor                 | 3 dB(A)                 |
| Noise sound power              | 102 dB(A)               |
| Vibration: Drilling into metal | 2.5 m/sec <sup>2</sup>  |

### USER BENEFITS

- Modified operation-mode change lever enables switch from 'Rotation' to 'Hammering' mode and vice-versa without rotating the chuck.
- 3 mode operation: Rotation only / Rotation with hammering / Hammering only
- One touch sliding chuck for easy bit installation and removal.
- Variable speed control by trigger
- Forward / reverse rotation
- Torque limiter
- Double Insulation
- 40 different bit angle settings
- Compact and lightweight design
- Depth stop
- Ergonomically designed handle with rubberised soft grip fits your hand perfectly to provide maximum control and comfort.

Link to product - [www.makitauk.com](http://www.makitauk.com)

