

Extruded Heat Sink Cases



Features:

- Silver anodized aluminium extruded box section to take 55 × 40 mm, 55 × 80 mm or 55 × 120 mm circuit boards
- Idea for small circuits, R.F amplifiers etc
- The maximum height of components on a board mounted in the bottom slot is 18 mm / 20 mm depending on orientation
- This box features dovetail slots down the side which accept a Linc-Lug mounting bracket to facilitate surface mounting
- Optional gaskets allow waterproofing
- One side of the box features two sets of appearance enhancing groves
- Between the sets of groves is a shallow (0.5 mm deep) recess which could be used for a label

Specifications:

Length Tolerance	: Nominal length -0 mm / +1 mm
Non-standard Lengths	: Available
Material	: Aluminium 6063 T6 (HE9)
Finish	: Silver anodized 5µm thickness to BS 1615 - can be painted directly if required. The inside and cut ends are not anodized
Weight	: 1 Kg/m
Perimeter	: 220 mm (outside), 217 mm (inside)
Screw ports	: Nominal diameter 2.7mm to take a No.4 self-tapping screw with 3 mm major diameter of a type normally used for plastic. They are not suitable for ordinary self-tapping screws that have a 2.9 mm diameter with wide tolerance. The screw ports can be threaded M3 using a thread-rolling tap, but a thread cutting tap will make a weak thread. Alternatively an M3 thread-forming screw can be used to roll its own thread