## Defence Standard 61-12 Part 5 Multicore Cables

## multicomp PRO

RoHS

**Compliant** 



### Application

These Multi-Core flexible cables are designed for high density wiring between components and within instruments and electronic equipment. They are extensively used in aircraft, process control systems, computers, data processors, military vehicles and military equipment.

### Standards

Defence Standard 61-12 Part 5

### Characteristics

Voltage Rating 440V r.m.s. at frequencies up to 1.6kHz

Maximum Resistance of Conductor at 20°C 16/0.2 : 40.1Ω/km

Current Carrying Capacity 2.5 Amps

**Temperature Rating** Fixed: -30°C to + 70°C Flexed: -15°C to +70°C

**Minimum Bending Radius** Fixed: 7.5 x overall diameter

#### Construction

**Conductor** Class 5 flexible tinned copper conductor; 0.5mm<sup>2</sup> (16/0.2mm)

Insulation PVC (Polyvinyl Chloride)

Screen TCWB (Tinned Copper Wire Braid)

**Sheath** PVC (Polyvinyl Chloride)

Sheath Colour Black, Grey

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

# multicomp PRO

## Defence Standard 61-12 Part 5 Multicore Cables

### Dimensions

Circular Conductor, PVC Insulated, PVC Sheathed, Def Stan 61/12 Part 4

Part Number	Colour	Length	Cable Identification Code	No. of Cores	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
MP002381		25	16-2-2A	2	0.8	5.5	31.97
MP002382		100	10-2-2A	2	0.0	5.5	51.97
MP002383		25	- 16-2-3A	3	0.8	5.8	39.59
MP002384		100		5	0.8		
MP002385		25	16-2-4A 4		0.85	6.3	49.49
MP002386		100		4			
MP002387		25	- 16-2-6A	6	0.85	7.3	69.9
MP002388	Black	100					
MP002389	DIACK	25		8	1	8.5	96.2
MP002390		100	10-2-0A				
MP002391	]	25	16-2-12A 12	10	1.1	9.5	125.6
MP002392		100		12			
MP002393		25	16-2-18A	18	1.1	11	178.2
MP002394		100					
MP002395		25	16-2-25A	25	1.2	13.1	244
MP002396		100	10-2-20A	25	1.2	13.1	244

#### Circular Conductor, PVC Insulated, Collectively Screened Cores, PVC Sheathed, Def Stan 61/12 Part 5

Part Number	Colour	Length	Cable Identification Code	No. of Cores	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
MP002397		25	16-2-2C	2	1	6.5	48.58
MP002398		100	10-2-20				
MP002399		25	40.0.00		1	6.8	55.24
MP002400		100	16-2-3C	3			
MP002401	1	25	16-2-4C	4	1	7.3	65.24
MP002402		100					
MP002403	Black	25	40.0.00	6	1	8.3	88.84
MP002404		100	16-2-6C	6			
MP002405	1	25	40.0.00		1.2	8.8	103.22
MP002406		100	16-2-8C	8			
MP002407	1	25	40.0.400	12	1.2	10.5	138.66
MP002408		100	16-2-12C				
MP002409		25	16-2-18C	18	1.2	12	193.47

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



## Defence Standard 61-12 Part 5 Multicore Cables

Part Number	Colour	Length	Cable Identification Code	No. of Cores	Nominal Thickness of Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/km
MP002304	1	25	16-2-4C	4	1	7.3	65.24
MP002305		100					
MP002306	- Grey	25	16-2-6C	6	1	8.3	88.84
MP002307		100					
MP002308		25	16-2-12C	10	1.2	10.5	138.66
MP002309		100		12			
MP002310		25	16-2-18C	18	1.2	12	193.47
MP002311		100					

### **Core Identification**

No. of Cores	Core Identification	No. of Cores	Core Identification	No. of Cores	Core Identification
1	Red	11	Turquoise	21	Blue/Black
2	Blue	12	Grey	22	Orange/Blue
3	Green	13	Red/Blue	23	Green/Blue
4	Yellow	14	Green/Red	24	Grey/Blue
5	White	15	Yellow/Red	25	Yellow/Green
6	Black	16	White/Red		
7	Brown	17	Red/Black		
8	Violet	18	Red/Brown		
9	Orange	19	Yellow/Blue		
10	Pink	20	White/Blue		

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

