

Palm Size Digital Multimeter



Description

The new generation Palm Size Multimeters redefines the performance standards for entry-level digital multimeters. This model ensures that users can work safely in CAT II 250V environment.

Features

- Clear LCD Display
- Equipped with Comfortable Protective Cover, Test Probe Holder
- 2 Meters Drop Test, Precision Protection
- Auto Power Off
- Auto Backlight Off
- Loud Buzzer Sound
- Knobs Shift Smoothly, In-line with Ergonomics

Specification Table

Characteristics	72-13430	72-13435	72-13440
Max Display		1999	
Range Selection	Auto	Manual	
Diode Test		✓	
Continuity Buzzer		✓	
Overload Alarm		✓	
Data Hold		✓	
Relative Mode	✓	-	
Low Battery Indication		✓	
NCV	-	-	✓
DC Voltage	200mV/2V/20V/200V/250V, ±(0.8%+1)	200mV/2000mV/20V/200V/250V, ±(0.5%+2)	200mV/2000mV/20V/250V, ±(0.5%+2)
AC Voltage	200mV/2V/20V/200V/250V, ±(1%+2)	200V/250V, ±(1.2%+3)	200V/250V, ±(1.2%+10)
AC Current	200µA/2000µA/20mA/ 200mA/2A/10A, ±(1.2%+3)	-	-
DC Current	200µA/2000µA/20mA/ 200mA/2A/10A, ±(1%+3)	2000µA/20mA/ 200mA/10A, ±(1%+3)	2000µA/20mA/ 200mA/10A, ±(1%+3)
Capacitance	2nF/20nF/200nF/2uF/ 20uF/200uF, ±(3%+5)	-	-



i. These

00V/250V,

l

A/

,